












Neutral conductor/PE terminal, continuous, for Front mounting, Up to 32 A, accessory for main and emergency switching-off switch 3LD2

Model							
product brand name	SETRON						
product designation	Neutral conductor/PE terminal						
design of the product	accessories for 3LD2 main and EMERGENCY-STOP switches						
AWG number / as coded connectable conductor cross section							
• minimum	14						
• maximum	8						
type of connectable conductor cross-sections / for main contacts							
• finely stranded / with core end processing	1x (1.5 ... 16 mm ²)						
• solid or stranded	1x (1.5...10 mm ²)						
General Product Approval							
	<table border="1"> <thead> <tr> <th>Test Certificates</th> <th>other</th> </tr> </thead> <tbody> <tr> <td>  Confirmation </td> <td>   </td> </tr> <tr> <td> Special Test Certificate </td> <td> Miscellaneous </td> </tr> </tbody> </table>	Test Certificates	other	 Confirmation	 	Special Test Certificate	Miscellaneous
Test Certificates	other						
 Confirmation	 						
Special Test Certificate	Miscellaneous						



[Confirmation](#)



[Special Test Certificate](#)

[Miscellaneous](#)

other

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD9220-2B>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3LD9220-2B>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD9220-2B

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

