



Auxiliary switch, 1NO+1NC 20-150ms leading, for four-hole front mounting, for floor mounting and encapsulated switches, accessory for main and emergency off switch 3LD2 for 160 - 250A and for molded case switch 3LD5 UL for 100A-150A

Model	
product brand name	SENTRON
product designation	Auxiliary switch, leading
design of the product	accessories for 3LD2 main and EMERGENCY-STOP switches, 3LD2 maintenance and repair switches with EMC shield plate
operational current	<ul style="list-style-type: none"> <li>• at AC-15 / at 48 V / rated value 10 A</li> <li>• at AC-15 / at 110 V / rated value 6 A</li> <li>• at AC-15 / at 230 V / rated value 3 A</li> <li>• at AC-15 / at 400 V / rated value 1.7 A</li> <li>• at AC-15 / at 500 V / rated value 1.5 A</li> <li>• at DC-13 / at 110 V / rated value 0.25 A</li> <li>• at DC-13 / at 48 V / rated value 0.5 A</li> <li>• at DC-13 / at 24 V / rated value 1 A</li> </ul>
lead time / relating to main contacts	20 ms
type of connectable conductor cross-sections / for auxiliary contacts	<ul style="list-style-type: none"> <li>• solid 1x (0.75 ... 2.5 mm<sup>2</sup>)</li> <li>• finely stranded / with core end processing 1x (0.75 ... 2.5 mm<sup>2</sup>)</li> <li>• stranded 1x (0.75 ... 2.5 mm<sup>2</sup>)</li> </ul>

General Product Approval

Declaration of Conformity



[Confirmation](#)



Test Certificates other

[Special Test Certificate](#)   
 [Environmental Confirmations](#)   
 [Miscellaneous](#)

Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**  
<http://www.siemens.com/lowvoltage/catalogs>  
**Industry Mall (Online ordering system)**  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3LD9240-5D>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3LD9240-5D>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3LD9240-5D](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD9240-5D)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



