



Neutral conductor/PE terminal, continuous, for front mounting, accessory for main and emergency switching-off switch 3LD25 for 63A and for molded case switch 3LD5 UL for 30A

| Model | |
|--|--|
| product brand name | SETRON |
| product designation | Neutral conductor/PE terminal |
| design of the product | accessories for 3LD25 main and EMERGENCY-STOP switches |
| AWG number / as coded connectable conductor cross section | |
| • minimum | 14 |
| • maximum | 6 |
| type of connectable conductor cross-sections / for main contacts | |
| • finely stranded / with core end processing | 1x (2.5...35 mm ²) |
| • solid or stranded | 1x (2.5 ... 16 mm ²) |

| General Product Approval | Declaration of Conformity |
|--------------------------|---------------------------|
|--------------------------|---------------------------|



[Confirmation](#)



| Test Certificates | other |
|-------------------|-------|
|-------------------|-------|

[Special Test Certificate](#)

[Environmental Confirmations](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD9250-2BA>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3LD9250-2BA>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD9250-2BA

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

