SIEMENS

Data sheet 3LD9280-5DF



Auxiliary switch, 1NO+1NC 20-150ms leading, with gold-plated contacts, four-hole front mounting, for floor mounting and encapsulated switches, for 16 - 125A, accessory for main and emergency off switch 3LD2 and for repair and maintenance switch 3LD2 with EMC plate

Model		
product brand name	SENTRON	
product designation	Auxiliary switch, leading	
design of the product	accessories for 3LD2 main and EMERGENCY-STOP switches, maintenance and repair switches with EMC shield plate	3LD2
operational current		
at AC-15 / at 48 V / rated value	10 A	
at AC-15 / at 110 V / rated value	6 A	
 at AC-15 / at 230 V / rated value 	3 A	
at AC-15 / at 400 V / rated value	1.7 A	
at AC-15 / at 500 V / rated value	1.5 A	
 at DC-13 / at 110 V / rated value 	0.25 A	
at DC-13 / at 48 V / rated value	0.5 A	
at DC-13 / at 24 V / rated value	1 A	
lead time / relating to main contacts	20 ms	
type of connectable conductor cross-sections / for auxiliary contacts		
• solid	1x (0.75 2.5 mm²)	
 finely stranded / with core end processing 	1x (0.75 2.5 mm²)	
stranded	1x (0.75 2.5 mm²)	
General Product Approval	Declaratio Conformit	





Confirmation







Conformity

Declaration of Conformity

Test Certificates

other

UK CA Special Test Certificate

Environmental Confirmations

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD9280-5DF

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3LD9280-5DF

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD9280-5DF

CAx-Online-Generator

http://www.siemens.com/cax

Tender specifications

http://www.siemens.com/specifications

⊘