



SENTRON, cylindrical fuse link, 22x58 mm, 25 A, aM, Un AC: 690 V

Model			
product brand name	SENTRON		
product designation	Cylindrical fuse link		
General technical data			
operating class of the fuse link	aM		
size of the fuse link	22x58 mm		
type of voltage / of the operating voltage	AC		
supply voltage / at DC	250 V		
operating voltage / at AC / rated value	690 V		
Dissipation			
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.55 W		
operational current / at AC / rated value	25 A		
Main circuit			
operational current / rated value	25 A		
Product details			
product component / striker	No		
Mechanical Design			
mounting position	Any, preferably vertical		
net weight	52 g		
General Product Approval	Declaration of Conformity	Test Certificates	other

[Confirmation](#)



[Miscellaneous](#)

[Miscellaneous](#)

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3NW8210-1>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3NW8210-1>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=3NW8210-1](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3NW8210-1)

**CAx-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



