












SENTRON, cylindrical fuse link, 10 x 38 mm, 32 A, aM, Un AC: 400 V

Model				
product brand name	SENTRON			
product designation	Cylindrical fuse link			
General technical data				
operating class of the fuse link	aM			
size of the fuse link	10x38 mm			
type of voltage / of the operating voltage	AC			
supply voltage / at DC	250 V			
operating voltage / at AC / rated value	400 V			
Dissipation				
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.8 W			
operational current / at AC / rated value	32 A			
Main circuit				
operational current / rated value	32 A			
Product details				
product component / striker	No			
Mechanical Design				
mounting position	Any, preferably vertical			
net weight	8 g			
General Product Approval				
<table border="0" style="width: 100%;"> <tr> <td style="width: 33%;">Confirmation</td> <td style="width: 33%; text-align: center;">    </td> <td style="width: 33%; text-align: right;">Miscellaneous</td> </tr> </table>		Confirmation	  	Miscellaneous
Confirmation	  	Miscellaneous		
Declaration of Conformity				
other				

Further information

- Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3NW8012-1>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3NW8012-1>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3NW8012-1
- CAx-Online-Generator
<http://www.siemens.com/cax>
- Tender specifications
<http://www.siemens.com/specifications>



