



LV HRC fuse base Sz. 1, 1-pole 250 A 690 V (1000 V) flat terminal

Model	
product brand name	SETRON
product designation	LV HRC fuse system
design of the thread / of the connection screw	M10
design of the product	LV HRC fuse base
General technical data	
number of poles	1
size of fuse system / according to EN 60269-1	NH1
utilization category	Without
Supply voltage	
supply voltage	
• at AC / rated value	690 V
• at DC	440 V
Current	
operational current	
• at 35 °C / rated value	235 A
• at 40 °C / rated value	230 A
• at 45 °C / rated value	222.6 A
• at 50 °C / rated value	215 A
• at 55 °C / rated value	207.6 A
• at 60 °C / rated value	202.6 A
• at 65 °C / rated value	192.6 A
• at 70 °C / rated value	185 A
• at AC / rated value	250 A
Product details	
product component / swivel-in mechanism	No
breaking capacity maximum short-circuit current (I _{cu})	
• at AC / rated value	120 kA
• at DC / rated value	25 kA
Connections	
tightening torque / with screw-type terminals / maximum	38 N·m
type of electrical connection	With flat-type terminal
• for main current circuit	flat connector
Mechanical Design	
fastening method	fixed mounting
fastening method / bus-mounting	No
net weight	760 g
General Product Approval	
Declaration of Conformity	



[Confirmation](#)



Test Certificates

Marine / Shipping

other

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



[Environmental Confirmations](#)

[Miscellaneous](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NH3230>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NH3230>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NH3230

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



