



LV HRC fuse base Size 1L 250 A 1000 V for photovoltaic applications

Model		
product brand name	SETRON	
product designation	LV HRC fuse system	
design of the thread / of the connection screw	M10	
design of the product	LV HRC fuse bases with swivel mechanism	
General technical data		
number of poles	1	
size of fuse system / according to EN 60269-1	NH1L	
Supply voltage		
supply voltage		
• at DC	1 000 V	
Current		
operational current		
• at 35 °C / rated value	235 A	
• at 40 °C / rated value	230 A	
• at 45 °C / rated value	222.6 A	
• at 50 °C / rated value	215 A	
• at 55 °C / rated value	207.6 A	
• at 60 °C / rated value	202.6 A	
• at 65 °C / rated value	192.6 A	
• at 70 °C / rated value	185 A	
• at AC / rated value	250 A	
Product details		
product component / swivel-in mechanism	Yes	
breaking capacity maximum short-circuit current (I <sub>cu</sub> )		
• at DC / rated value	25 kA	
Connections		
tightening torque / with screw-type terminals / maximum	20 N·m	
type of electrical connection	for mounting on mounting plate	
• for main current circuit	flat connector	
Mechanical Design		
height	306 mm	
width	71 mm	
depth	130 mm	
fastening method	fixed mounting	
fastening method / bus-mounting	No	
net weight	1 306 g	
<b>General Product Approval</b>	<b>Declaration of Conformity</b>	<b>other</b>

[Confirmation](#)



[Miscellaneous](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NH7260-4>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3NH7260-4>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NH7260-4](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NH7260-4)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



