



Device adapter S00/S0, 25A, for 60 mm busbar system, 45x 200 mm long special lines welded-on AWG 12, 99 mm long spacer enclosed Mounting rail screwed on

Model	
product brand name	SETRON
product designation	Device adapter
design of the product	Accessories
operational current / at AC / rated value	25 A
number of mounting rails	1
Connections	
type of electrical connection	AWG 12
Mechanical Design	
height	200 mm
width / of the adapter	45 mm
depth	63 mm
thickness / of the busbar	
• minimum	5 mm
• maximum	10 mm
busbar center-to-center spacing	60 mm
net weight	308 g
General Product Approval	



[Confirmation](#)



General Product Approval	Declaration of Conformity	Test Certificates		
			Type Test Certificates/Test Report	Special Test Certificate
				Miscellaneous

Marine / Shipping



Marine / Shipping

other

Railway



[Confirmation](#)

[Miscellaneous](#)

[Vibration and Shock](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1251-5DS10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1251-5DS10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1251-5DS10

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



