



SITOR cylindrical fuse link, 10 x 38 mm, 20 A, gR, Un AC: 690 V, Un DC: 250 V

Model	
product brand name	SETRON
product designation	SITOR cylindrical fuse link
General technical data	
operating class of the fuse link	gR
size of the fuse link	10x38 mm
type of voltage / of the operating voltage	AC
supply voltage / at DC	250 V
operating voltage / at AC / rated value	690 V
operational current / at AC / rated value	20 A
Main circuit	
operational current / rated value	20 A
Product details	
product component / striker	No
Mechanical Design	
mounting position	Any, preferably vertical
net weight	9 g
General Product Approval	
Declaration of Conformity	

[Confirmation](#)



[Miscellaneous](#)



Declaration of Conformity

other



[Miscellaneous](#)

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1020-0MK>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1020-0MK>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1020-0MK

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



