## **SIEMENS**

## **Data sheet**



Pushbutton, compact, with extended stroke (12 mm), 22 mm, round, plastic, black, pushbutton, raised, momentary contact type, with holder

| product brand name  | SIRIUS ACT                         |
|---|------------------------------------|
| product designation   | Pushbuttons                        |
| design of the product   | Complete unit                      |
| product type designation  | 3SU1                               |
| product line  | Plastic, black, 22 mm              |
| Enclosure   |                                    |
| number of command points  | 1                                  |
| Actuator  |                                    |
| design of the actuating element                                   | Raised button with extended stroke |
| principle of operation of the actuating element                   | momentary contact type             |
| product extension optional  |                                    |
| • light source  | No                                 |
| <ul> <li>contact module</li> </ul>                                | Yes                                |
| color of the actuating element                                    | black                              |
| material of the actuating element                                 | plastic                            |
| shape of the actuating element                                    | round                              |
| outer diameter of the actuating element                           | 29.5 mm                            |
| Front ring  |                                    |
| product component front ring                                      | Yes                                |
| design of the front ring  | Standard                           |
| material of the front ring  | plastic                            |
| color of the front ring   | black                              |
| General technical data  |                                    |
| protection class IP   | IP66, IP67, IP69(IP69K)            |
| degree of protection NEMA rating                                  | 1, 2, 3, 3R, 4, 4X, 12, 13         |
| shock resistance  |                                    |
| • acc. to IEC 60068-2-27  | sinusoidal half-wave 50g / 11 ms   |
| <ul> <li>for railway applications acc. to DIN EN 61373</li> </ul> | Category 1, Class B                |
| vibration resistance  |                                    |
| • acc. to IEC 60068-2-6   | 10 500 Hz: 5g                      |
| <ul> <li>for railway applications acc. to DIN EN 61373</li> </ul> | Category 1, Class B                |
| operating frequency maximum                                       | 3 600 1/h                          |
| mechanical service life (switching cycles) typical                | 5 000 000                          |
| reference code acc. to IEC 81346-2                                | S                                  |
| Substance Prohibitance (Date)                                     | 01.10.2014 00:00:00                |
| Ambient conditions  |                                    |
| ambient temperature   |                                    |
| <ul> <li>during operation</li> </ul>                              | -25 +70 °C                         |
| <ul> <li>during storage</li> </ul>                                | -40 +80 °C                         |

| environmental category during operation acc. to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %) |
|---|---|
| Installation/ mounting/ dimensions                        |   |
| height  | 40 mm   |
| width   | 30 mm   |
| shape of the installation opening                         | round   |
| mounting diameter   | 22.3 mm   |
| positive tolerance of installation diameter               | 0.4 mm  |
| mounting height   | 32.5 mm   |
| installation width  | 29.5 mm   |
| installation depth  | 30.9 mm   |
| Certificates/ approvals                                   |   |



**General Product Approval** 







**Declaration of Conformity** 

UK Declaration of Conformity Special Test Certificate

**Test Certificates** 

**Test Certificates** 

other

Type Test Certificates/Test Report

Confirmation

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10


Industry Mall (Online ordering system)


https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1200-0FB10-0AA0

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1200-0FB10-0AA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1200-0FB10-0AA0&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1200-0FB10-0AA0&lang=en</a>





last modified: 7/14/2021 🖸