

circuit breaker VL1250N standard breaking capacity I<sub>cu</sub>=55kA, 415V AC 3-pole, line protection trip unit ETU20, LSI I<sub>n</sub>=1000A, rated current I<sub>R</sub>=400...1000A, overload protection, ISD=1.5 to 10xI<sub>R</sub>, II=11 xI<sub>N</sub> short-circuit protection without auxiliary release without auxiliary/alarm switch

Model	
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU20
General technical data	
number of poles	3
size of the circuit-breaker	3VL7
mechanical service life (switching cycles) / typical	3 000
electrical endurance (switching cycles) / typical	1 500
utilization category	A
performance class for circuit breaker	N
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	Q
operating frequency / maximum	30 1/s
Voltage	
Rated operational voltage U <sub>e</sub> / max.	690 V
<ul style="list-style-type: none"> <li>insulation voltage / rated value</li> <li>insulation voltage (U<sub>i</sub>) / at AC / rated value</li> </ul>	800 V
surge voltage resistance / rated value	8 kV
operating voltage	
<ul style="list-style-type: none"> <li>rated value / maximum</li> <li>for main current circuit / at AC / at 50 Hz / maximum</li> <li>for main current circuit / at AC / at 60 Hz / maximum</li> </ul>	690 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LSI
Current	
operational current	
<ul style="list-style-type: none"> <li>at 40 °C / rated value</li> <li>at 45 °C / rated value</li> <li>at 50 °C / rated value</li> <li>at 55 °C / rated value</li> <li>at 60 °C / rated value</li> <li>at 65 °C / rated value</li> <li>at 70 °C / rated value</li> </ul>	1 000 A
continuous current / rated value	1 000 A
derating temperature / for the rated value of the continuous current	50 °C
adjustable current response value current	
<ul style="list-style-type: none"> <li>of the current-dependent overload release / full-scale value</li> <li>of instantaneous short-circuit trip unit / minimum</li> <li>of instantaneous short-circuit trip unit / maximum</li> </ul>	1 000 A
Main circuit	
operating frequency	
<ul style="list-style-type: none"> <li>1 / rated value</li> <li>2 / rated value</li> </ul>	50 Hz
	60 Hz
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0

number of NC contacts / for auxiliary contacts	0	
number of NO contacts / for auxiliary contacts	0	
<b>Suitability</b>		
suitability for use	system/generator protection	
<b>Adjustable parameters</b>		
adjustable current response value current / of the short-time delayed short-circuit release / full-scale value	10 000 A	
adjustable current response value current / of the current-dependent overload release / initial value	40 A	
<b>Product details</b>		
product component		
• trip indicator	No	
• auxiliary switch	No	
• voltage trigger	No	
• undervoltage release	No	
• undervoltage release with leading contact	No	
product extension / optional / motor drive	Yes	
<b>Product function</b>		
product function		
• of thermal overload trip unit	adjustable	
• grounding protection	No	
• for neutral conductors / short-circuit and overload proof	No	
• overload protection	Yes	
<b>Short circuit</b>		
breaking capacity operating short-circuit current (Ics)		
• at 240 V / rated value	35 kA	
• at 415 V / rated value	28 kA	
• at 500 V / rated value	20 kA	
• at 690 V / rated value	10 kA	
breaking capacity maximum short-circuit current (Icu)		
• at 240 V / rated value	65 kA	
• at 415 V / rated value	55 kA	
• at 440 V / rated value	35 kA	
• at 480 V / acc. to NEMA / rated value	25 kA	
• at 500 V / rated value	25 kA	
• at 600 V / acc. to NEMA / rated value	20 kA	
• at 690 V / rated value	20 kA	
<b>Connections</b>		
arrangement of electrical connectors / for main current circuit	front side	
type of connectable conductor cross-sections / for auxiliary contacts		
• solid	0.75 ... 1.5 mm <sup>2</sup>	
• finely stranded / with core end processing	0,75 ... 1.0 mm <sup>2</sup>	
type of electrical connection / for main current circuit	screw-type terminals	
<b>Mechanical Design</b>		
height	406.5 mm	
width	228.5 mm	
depth	333.5 mm	
fastening method	fixed mounting	
<b>Environmental conditions</b>		
ambient temperature / during operation		
• minimum	-25 °C	
• maximum	70 °C	
ambient temperature / during storage		
• minimum	-40 °C	
• maximum	80 °C	
<b>General Product Approval</b>	<b>EMC</b>	<b>Declaration of Conformity</b>



[Miscellaneous](#)

[TSE](#)



EG-Konf.

Test Certificates

Marine / Shipping

other

[Special Test Certificate](#)



RINA



RMRS



DNV-GL

[Environmental Confirmations](#)

[Confirmation](#)

other

[Miscellaneous](#)

[Miscellaneous](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL7710-1SE36-0AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3VL7710-1SE36-0AA0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL7710-1SE36-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL7710-1SE36-0AA0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



