

access.f. 3WL/3VL circ.-breaker capacitor storage unit f.shunt trip rated control voltage ac 50/60Hz 220-240V,DC 220-250V

Model			
product brand name	SENTRON		
product designation	Accessories		
design of the product	Auxiliary release		
General technical data			
closing apparent power [VA]	1 VA		
closing active power [W]	1 W		
opening time / of circuit breaker / at Us = 100%	80 ms		
storage period / at Us	5 min		
recharging time / at Us	5 s		
Voltage			
surge voltage resistance	4 kV		
Control current			
control supply voltage (Us) / at DC / rated value	220 to 250 V		
Adjustable parameters			
operating range / of the voltage trigger			
• minimum	0.85		
• maximum	1.1		
General Product Approval	EMC	Declaration of Conformity	Test Certificates

[Confirmation](#)



[UK Declaration of Conformity](#)



[Miscellaneous](#)

other

[Environmental Conformations](#)

[Miscellaneous](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL9111-0BA14-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL9111-0BA14-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL9111-0BA14-0AA0

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



