

accessories circuit breaker 3WL 1st trip signalling switch 1 CO; S24

Model			
product brand name	SENTRON		
product designation	1st trip alarm switch		
design of the product	Accessories		
General technical data			
degree of pollution	3		
Voltage			
surge voltage resistance / rated value	4 kV		
Supply voltage			
operating voltage			
<ul style="list-style-type: none"> at AC / at 50 Hz / rated value / maximum 	250 V		
<ul style="list-style-type: none"> at DC / rated value / maximum 	250 V		
Current			
operational current			
<ul style="list-style-type: none"> at AC-12 / at 230 V / rated value 	8 A		
<ul style="list-style-type: none"> at DC-12 / at 230 V / rated value 	0.2 A		
<ul style="list-style-type: none"> at DC-12 / at 110 V / rated value 	0.4 A		
<ul style="list-style-type: none"> at DC-12 / at 24 V / rated value 	6 A		
Short circuit			
design of the DIAZED fuse link gG / for short-circuit protection / maximum permissible	6 A Dz (quick)		
General Product Approval	EMC	Declaration of Conformity	Test Certificates

[Confirmation](#)



[UK Declaration of Conformity](#)



[Miscellaneous](#)

other

[Miscellaneous](#)

[Environmental Conformations](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL9111-0AH14-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL9111-0AH14-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/blddb/cax_en.aspx?mlfb=3WL9111-0AH14-0AA0

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



