



RC unit for 5SP4, 4-pole, type A, In: 100 A, 300 mA, Un AC: 400 V

Model	
product brand name	SENTRON
product designation	RCD-unit
design of the product	instantaneous
number of poles	4
size of installation devices / according to DIN 43880	1
mechanical service life (switching cycles) / typical	10 000
overvoltage category	III
degree of pollution	2
insulation voltage (Ui) / rated value	460 V
surge voltage resistance / rated value	4 000 V
protection function / false tripping	Yes
power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	5 W
• maximum	15 W
tripping fault current / rated value	300 mA
operational current	
• at 40 °C / rated value	93 A
• at 45 °C / rated value	93 A
• at 50 °C / rated value	90 A
• at 55 °C / rated value	87 A
• at 60 °C / rated value	85 A
• at 65 °C / rated value	83 A
• at 70 °C / rated value	80 A
• at AC / rated value	100 A
residual current type	A
surge current resistance / rated value	1 kA
product feature	
• OFF-delay time adjustable	No
• rated fault current adjustable	No
• sealable	No
connectable conductor cross-section / solid	
• minimum	6 mm ²
• maximum	50 mm ²
connectable conductor cross-section / stranded	
• minimum	6 mm ²
• maximum	50 mm ²
tightening torque / with screw-type terminals	
• minimum	2.5 N·m

<ul style="list-style-type: none"> • maximum 	3 N·m
height	90 mm
width	124 mm
depth	70 mm
installation depth	70 mm
number of modular width units	5
fastening method	REG
mounting position	any
net weight	682 g
ambient temperature / during operation <ul style="list-style-type: none"> • minimum • maximum 	-25 °C 45 °C
ambient temperature / during storage <ul style="list-style-type: none"> • minimum permissible • maximum permissible 	-40 °C 75 °C
number of test cycles / for environmental testing / according to IEC 60068-2-30	28
reference code <ul style="list-style-type: none"> • according to EN 61346-2 • according to IEC 81346-2 	F F

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SM2647-6>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SM2647-6>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM2647-6

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



