

compact Pin Busbar, 10mm<sup>2</sup> connection: 3p/N compact device 1 MW touch protected 1000mm cuttable



Model			
product brand name	SENTRON		
product designation	Pin busbar		
design of the product	10 mm <sup>2</sup> , 3p+N, 60MW, 12x compact, can be cut		
General technical data			
phase number	3		
cross-section	10 mm <sup>2</sup>		
operating voltage / rated value / maximum	230 V		
Main circuit			
operational current / rated value	63 A		
Suitability			
<b>suitability for interaction</b>			
• devices with auxiliary switch	No		
• devices with N conductor	Yes		
Product details			
product feature / insulated	Yes		
Number			
number of devices / suitable for fitting	60		
Connections			
type of electrical connection	Pin		
Mechanical Design			
module width	18 mm		
height	13 mm		
width	40.8 mm		
length	1 060 mm		
net weight	679 g		
General Product Approval		Declaration of Conformity	other

[Confirmation](#)

[Miscellaneous](#)



[UK Declaration of Conformity](#)

[Miscellaneous](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5ST3773-0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3773-0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3773-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3773-0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



