


compact Pin Busbar, 10mm² connection: 1p/N compact device 1 MW touch protected 1000mm cuttable



Model	
product brand name	SENTRON
product designation	Pin busbar
design of the product	10 mm ² , 1p+N, 60MW, 12x compact, can be cut
General technical data	
phase number	1
cross-section	10 mm ²
operating voltage / rated value / maximum	230 V
Main circuit	
operational current / rated value	63 A
Suitability	
suitability for interaction	
• devices with auxiliary switch	No
• devices with N conductor	Yes
Product details	
product feature / insulated	Yes
Number	
number of devices / suitable for fitting	60
Connections	
type of electrical connection	Pin
Mechanical Design	
module width	18 mm
height	13 mm
width	40.8 mm
length	1 060 mm
net weight	612 g
General Product Approval	
Declaration of Conformity	
other	

[Confirmation](#)

[Miscellaneous](#)



[UK Declaration of Conformity](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5ST3774-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3774-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3774-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



5ST3774-0

