


compact Pin Busbar, 10mm² connection: 3p/N (RCCB N-left) 1x RCCB 4-pole + 6x compact device 1MW touch protected 10 MW cuttable

Model	
product brand name	SENTRON
product designation	Pin busbar
design of the product	10 mm ² , 3p+N, RCCB N left 3p+N, 6x compact, can be cut
General technical data	
phase number	3
cross-section	10 mm ²
operating voltage / rated value / maximum	400 V
Main circuit	
operational current / rated value	63 A
Suitability	
suitability for interaction	
• devices with auxiliary switch	No
• devices with N conductor	Yes
Product details	
product feature / insulated	Yes
Number	
number of devices / suitable for fitting	7
Connections	
type of electrical connection	Pin
Mechanical Design	
module width	18 mm
height	13.7 mm
width	42.4 mm
length	180.8 mm
General Product Approval	
<div style="display: flex; justify-content: space-between;"> Confirmation Miscellaneous </div>	
Declaration of Conformity	
<div style="display: flex; justify-content: space-around; align-items: center;">  <div style="text-align: center;"> UK Declaration of Conformity </div> <div style="text-align: center;"> Miscellaneous </div> </div> <p style="text-align: center; font-size: small;">EG-Konf.</p>	
other	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3783-1KL>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3783-1KL>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3783-1KL

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



