


compact Pin Busbar, 10mm² connection: 3p/N (RCCB N-right) 1x RCCB 4-pole+1x MCB 3-pole+ 7x compact device 1MW touch protected 14 MW cuttable

Model	
product brand name	SENTRON
product designation	Pin busbar
design of the product	10 mm ² , 3p+N, RCCB N right 3p+N, MCB 3p, 7x compact, can be cut
General technical data	
phase number	3
cross-section	10 mm ²
operating voltage / rated value / maximum	400 V
Main circuit	
operational current / rated value	63 A
Suitability	
suitability for interaction	
• devices with auxiliary switch	No
• devices with N conductor	Yes
Product details	
product feature / insulated	Yes
Number	
number of devices / suitable for fitting	9
Connections	
type of electrical connection	Pin
Mechanical Design	
module width	18 mm
height	13.7 mm
width	42.4 mm
length	252.8 mm
General Product Approval	
Confirmation Miscellaneous UK Declaration of Conformity	
Declaration of Conformity	
 <small>EG-Konf.</small>	
other	
Miscellaneous	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3785-4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3785-4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3785-4

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



