

Pin Busbar, 10mm² connection: 3p (RCCB N-right) 1x RCCB 4-pole + 6x MCB 1-pole touch protected 10 MW fixed length

Model		
product brand name	SENTRON	
product designation	Pin busbar	
design of the product	10 mm ² , 3p, RCCB N right 3p+N, 6x MCB 1-p, without neutral, cannot be cut	
General technical data		
phase number	3	
cross-section	10 mm ²	
operating voltage / rated value / maximum	400 V	
Main circuit		
operational current / rated value	63 A	
Suitability		
suitability for interaction		
<ul style="list-style-type: none"> • devices with auxiliary switch • devices with N conductor 	<p>No</p> <p>No</p>	
Product details		
product feature / insulated	Yes	
Number		
number of devices / suitable for fitting	7	
Connections		
type of electrical connection	Pin	
Mechanical Design		
module width	18 mm	
height	15.2 mm	
width	8.6 mm	
length	176 mm	
General Product Approval	Declaration of Conformity	other

[Confirmation](#)

[Miscellaneous](#)



[UK Declaration of Conformity](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3624-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3624-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3624-1

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

