

Compact pin busbar, 10mm<sup>2</sup> connection 3p/N 14x compact device 1 MW touch protected 14 MW fixed length



Model	
product brand name	SENTRON
product designation	Pin busbar
design of the product	10 mm <sup>2</sup> , 3p+N, 14MW, 14x compact
General technical data	
phase number	3
cross-section	10 mm <sup>2</sup>
operating voltage / rated value / maximum	230 V
Main circuit	
operational current / rated value	63 A
Suitability	
<b>suitability for interaction</b>	
• devices with auxiliary switch	No
• devices with N conductor	Yes
Product details	
product feature / insulated	Yes
Number	
number of devices / suitable for fitting	14
Connections	
type of electrical connection	Pin
Mechanical Design	
module width	18 mm
height	13.7 mm
width	42.4 mm
length	253 mm
net weight	212 g
General Product Approval	
Declaration of Conformity	
other	

[Confirmation](#)

[Miscellaneous](#)



[UK Declaration of Conformity](#)



[Miscellaneous](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5ST3673-4>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3673-4>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3673-4](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3673-4)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



