

Compact pin busbar, 10mm² connection +/-AS 12x CBE 1 MW touch protection 12 MW fixed length



Model					
product brand name	SENTRON				
product designation	Pin busbar				
design of the product	10 mm ² , 12MW, 12x CBE				
General technical data					
phase number	1				
cross-section	10 mm ²				
Main circuit					
operational current / rated value	63 A				
Suitability					
suitability for interaction					
• devices with auxiliary switch	Yes				
• devices with N conductor	No				
Product details					
product feature / insulated	Yes				
Number					
number of devices / suitable for fitting	12				
Connections					
type of electrical connection	Pin				
Mechanical Design					
module width	18 mm				
height	13.7 mm				
width	42.4 mm				
length	217.8 mm				
net weight	105 g				
General Product Approval					
<table border="1"> <thead> <tr> <th>Declaration of Conformity</th> <th>other</th> </tr> </thead> <tbody> <tr> <td> Confirmation </td> <td> Miscellaneous </td> </tr> </tbody> </table>		Declaration of Conformity	other	Confirmation	Miscellaneous
Declaration of Conformity	other				
Confirmation	Miscellaneous				



[UK Declaration of Conformity](#)



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mf=5ST3674-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3674-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3674-1

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



