

compact Pin Busbar, 10mm² connection: 1p/N 6x AFDD + 6x compact device 1 MW touch protected 12 MW fixed length



Model					
product brand name	SENTRON				
product designation	Pin busbar				
design of the product	10 mm ² , 1p+N, 12MW, 6x AFDD 5SM6 + 6x compact				
General technical data					
phase number	1				
cross-section	10 mm ²				
operating voltage / rated value / maximum	230 V				
Main circuit					
operational current / rated value	63 A				
Suitability					
suitability for interaction					
• devices with auxiliary switch	No				
• devices with N conductor	Yes				
Product details					
product feature / insulated	Yes				
Number					
number of devices / suitable for fitting	6				
Connections					
type of electrical connection	Pin				
Mechanical Design					
module width	36 mm				
height	13.7 mm				
width	42.4 mm				
length	200.2 mm				
net weight	84 g				
General Product Approval		Declaration of Conformity		other	

[Confirmation](#)

[Miscellaneous](#)



[UK Declaration of Conformity](#)



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5ST3676-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3676-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3676-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





