

Pin busbar, 3-phase 10 mm<sup>2</sup>, 58 MW, gray insulation can be cut for AFDD 5SM601.-2, pole center distance at least 150 mm



Model		
product brand name	SENTRON	
product designation	Pin busbar	
design of the product	3PH 10 mm <sup>2</sup> , 58MW gray	
General technical data		
phase number	3	
cross-section	10 mm <sup>2</sup>	
Main circuit		
operational current / rated value	63 A	
Product details		
product feature / insulated	Yes	
Connections		
type of electrical connection	Pin	
Mechanical Design		
width	14 mm	
length	1 032.4 mm	
General Product Approval		
	Declaration of Conformity	other

[Confirmation](#)

[Miscellaneous](#)



[Miscellaneous](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3740-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3740-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3740-1](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3740-1)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



