



compensator for remote control switch 5TT41.. for glow lamp current 20 mA

Model	
product brand name	SETRON
product designation	Remote control switch
latching relay design	others
Voltage	
type of voltage / of the operating voltage	AC
continuous voltage fuse version	Yes
supply voltage	250 V
Supply voltage	
supply voltage / minimum	250 V
Protection class	
protection class IP	IP20, with connected conductors
Switching capacity	
switching capacity current	16 A
• at cos phi 0.6	
Control current	
control voltage frequency	50 Hz
• _1 / initial value	
• _1 / full-scale value	50 Hz
Number	
number of terminals	2
Connections	
connectable conductor cross-section / for flexible conductor / with core end processing	1 mm <sup>2</sup> 6 mm <sup>2</sup>
• minimum	
• maximum	6 mm <sup>2</sup>
connectable conductor cross-section / for rigid conductor	1.5 mm <sup>2</sup> 6 mm <sup>2</sup>
• minimum	
• maximum	6 mm <sup>2</sup>
Mechanical Design	
mounting height	90 mm
installation depth	70 mm
number of modular width units	1
fastening method	DIN rail
mounting position	any
net weight	73 g
Environmental conditions	
ambient temperature / during operation	

- minimum
- maximum

-10 °C  
40 °C

General Product Approval

Declaration of Conformity

other

[Confirmation](#)

[Miscellaneous](#)

EAC

UK  
CA

CE  
EG-Konf.

[Confirmation](#)

other

[Miscellaneous](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT4920>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT4920>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TT4920](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4920)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



