



Auxiliary current switch Contact for AC 6 A, 250V 1 NO 1 NC

Model	
product brand name	SETRON
product designation	Remote control switch
latching relay design	Auxiliary switch
General technical data	
galvanic isolation / between magnet coil and contact	Yes
switching voltage / of the contacts / at AC / minimum	10 V
switching current / at AC / per contact / minimum	100 mA
Voltage	
type of voltage / of the operating voltage	AC
Protection class	
protection class IP	IP20
Product details	
number of NC contacts	1
number of NO contacts	1
number of CO contacts	0
pulse duration / minimum	50 ms
Mechanical Design	
height	90 mm
width	9 mm
width of opening / of the contacts	1.2 mm
depth	73 mm
mounting height	90 mm
installation depth	73 mm
number of modular width units	0.5
fastening method	DIN rail
mounting position	Horizontal and vertical
net weight	45 g
Environmental conditions	
ambient temperature / during operation	
• minimum	-25 °C
• maximum	70 °C
General Product Approval	
Declaration of Conformity	
other	

[Confirmation](#)



[Miscellaneous](#)

[Confirmation](#)

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5TT4930>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5TT4930>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5TT4930](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5TT4930)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



