



auxiliary current switch, group half module

Model	
product brand name	SETRON
product designation	Remote control switch
latching relay design	Mechanical for group control
General technical data	
galvanic isolation / between magnet coil and contact	Yes
switching voltage / of the contacts / at AC / minimum	10 V
switching current / at AC / per contact / minimum	100 mA
Voltage	
type of voltage / of the operating voltage	AC
Protection class	
protection class IP	IP20
Switching capacity	
switching capacity current	16 A
• at cos phi 0.6	
Product details	
number of NC contacts	0
number of NO contacts	0
number of CO contacts	0
Product function	
product function / direct operation	Yes
pulse duration / minimum	50 ms
Mechanical Design	
height	90 mm
width	9 mm
width of opening / of the contacts	1.2 mm
depth	73 mm
mounting height	90 mm
installation depth	73 mm
number of modular width units	0.5
fastening method	DIN rail
mounting position	Horizontal and vertical
net weight	47 g
Environmental conditions	
ambient temperature / during operation	-25 °C 70 °C
• minimum	
• maximum	
General Product Approval	
Declaration of Conformity	
other	



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT4932>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT4932>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4932

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



