



Remote control switch with 4 NO contacts Contact for 230 V AC, 400V 16A
Control 110V DC

Model	
product brand name	SETRON
product designation	Remote control switch
latching relay design	Mechanical switch
General technical data	
electrical endurance (switching cycles)	50 000
galvanic isolation / between magnet coil and contact	Yes
switching voltage / of the contacts / at AC / minimum	10 V
switching current / at AC / per contact / minimum	100 mA
power loss [V·A] / of magnet coil / with pulse / rated value	7 VA
Voltage	
type of voltage / of the operating voltage	DC
continuous voltage fuse version	Yes
operating range factor control supply voltage rated value / at AC / at 50 Hz	
• initial value	0.8
• full-scale value	1.1
surge voltage resistance / rated value	4 kV
supply voltage	400 V
Supply voltage	
supply voltage / minimum	250 V
Protection class	
protection class IP	IP20, with connected conductors
Switching capacity	
switching capacity apparent power	
• for fluorescent lamp load with DUO circuit	900 VA
• for fluorescent lamp load with parallel compensation	400 VA
• for uncompensated fluorescent lamp load	500 VA
switching capacity current	
• at cos phi 0.6	16 A
• rated value	16 A
switching capacity active power / with incandescent lamp load	2 000 W
Dissipation	
power loss [W]	
• at 16 A / per contact / rated value	1.2 W
switching current	
• with glow lamp load / with 5TT4 920 compensating capacitor	25 mA

<ul style="list-style-type: none"> with glow lamp load 	5 mA
Control current	
type of voltage	DC
<ul style="list-style-type: none"> of control voltage_1 	DC
control voltage	
<ul style="list-style-type: none"> _1 / initial value 	88 V
<ul style="list-style-type: none"> _1 / full-scale value 	121 V
<ul style="list-style-type: none"> _1 / setpoint 	110 V
control voltage frequency	
<ul style="list-style-type: none"> _1 / initial value 	50 Hz
<ul style="list-style-type: none"> _1 / full-scale value 	50 Hz
Product details	
product component / switch position indicator	Yes
number of NC contacts	0
number of NO contacts	4
number of CO contacts	0
Product function	
product function / direct operation	Yes
pulse duration / minimum	50 ms
Number	
number of terminals	10
Connections	
connectable conductor cross-section / for flexible conductor / with core end processing	
<ul style="list-style-type: none"> minimum 	1 mm ²
<ul style="list-style-type: none"> maximum 	6 mm ²
connectable conductor cross-section / for rigid conductor	
<ul style="list-style-type: none"> minimum 	1 mm ²
<ul style="list-style-type: none"> maximum 	6 mm ²
tightening torque / with screw-type terminals	
<ul style="list-style-type: none"> minimum 	0.8 N·m
<ul style="list-style-type: none"> maximum 	1 N·m
Mechanical Design	
width of opening / of the contacts	1.2 mm
mounting height	90 mm
installation depth	70 mm
number of modular width units	2
fastening method	DIN rail
mounting position	any
required spacing / for live parts	6 mm
net weight	215 g
Environmental conditions	
ambient temperature / during operation	
<ul style="list-style-type: none"> minimum 	-10 °C
<ul style="list-style-type: none"> maximum 	40 °C
General Product Approval	
Declaration of Conformity	
Test Certificates	

[Confirmation](#)



[Miscellaneous](#)

other

[Confirmation](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT4114-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT4114-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4114-1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



