



Remote control switch Contact for 25 A Voltage 24 V AC 1 NO 1 NC

Model	
product brand name	SETRON
product designation	Remote control switch
latching relay design	Mechanical switch
General technical data	
electrical endurance (switching cycles)	50 000
galvanic isolation / between magnet coil and contact	Yes
switching voltage / of the contacts / at AC / minimum	10 V
switching current / at AC / per contact / minimum	100 mA
power loss [V·A] / of magnet coil / with pulse / rated value	18 VA
Voltage	
type of voltage / of the operating voltage	AC
continuous voltage fuse version	Yes
surge voltage resistance / rated value	3 kV
supply voltage	400 V
Supply voltage	
supply voltage / minimum	230 V
Protection class	
protection class IP	IP20
Switching capacity	
switching capacity apparent power	
• for fluorescent lamp load with DUO circuit	2 436 VA
• for fluorescent lamp load with parallel compensation	986 VA
• for uncompensated fluorescent lamp load	1 624 VA
switching capacity current	
• at cos phi 0.6	25 A
• rated value	25 A
switching capacity active power / with incandescent lamp load	5 500 W
Dissipation	
power loss [W]	
• at 16 A / per contact / rated value	2 W
• of magnet coil / with pulse / rated value	13 W
Control current	
type of voltage	
• of control voltage_1	AC
control voltage	
• _1 / initial value	207 V
• _1 / full-scale value	253 V

<ul style="list-style-type: none"> <li>• _1 / setpoint</li> </ul>	24 V		
control voltage frequency			
<ul style="list-style-type: none"> <li>• _1 / initial value</li> <li>• _1 / full-scale value</li> </ul>	50 Hz 60 Hz		
<b>Product details</b>			
product component / switch position indicator	Yes		
number of NC contacts	1		
number of NO contacts	1		
number of CO contacts	0		
<b>Product function</b>			
product function / direct operation	Yes		
pulse duration / minimum	50 ms		
<b>Number</b>			
number of terminals	4		
<b>Connections</b>			
connectable conductor cross-section / for flexible conductor / with core end processing			
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	1 mm <sup>2</sup> 10 mm <sup>2</sup>		
connectable conductor cross-section / for rigid conductor			
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	1 mm <sup>2</sup> 10 mm <sup>2</sup>		
<b>Mechanical Design</b>			
height	90 mm		
width	17.5 mm		
width of opening / of the contacts	3 mm		
depth	73 mm		
mounting height	90 mm		
installation depth	73 mm		
number of modular width units	1		
fastening method	DIN rail		
mounting position	Horizontal and vertical		
net weight	166 g		
<b>Environmental conditions</b>			
ambient temperature / during operation			
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	-25 °C 55 °C		
<b>General Product Approval</b>	<b>Declaration of Conformity</b>	<b>Test Certificates</b>	<b>other</b>

[Confirmation](#)



[Miscellaneous](#)

[Confirmation](#)

**other**

[Miscellaneous](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5TT4425-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT4425-2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TT4425-2](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4425-2)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



