



Phase signaling device 3 lamps 230 V 3x green

Model		
product brand name	SETRON	
product designation	5TE5 indicator lights	
design of the product	LED signal detector	
type of light source	LED	
socket design / for light source	others	
type of voltage / of the operating voltage	AC	
Supply voltage		
operating voltage		
• rated value / minimum	230 V	
• rated value / maximum	230 V	
• at AC / rated value	230 V	
Protection class		
protection class IP	IP20	
Appearance		
color / of the lens	Green	
Number		
number of terminals / with cross-head screw	1	
Connections		
connectable conductor cross-section / for flexible conductor / with core end processing		
• minimum	1 mm ²	
• maximum	6 mm ²	
connectable conductor cross-section / for rigid conductor		
• minimum	1.5 mm ²	
• maximum	6 mm ²	
tightening torque / with screw-type terminals / maximum	1.2 N·m	
Mechanical Design		
installation depth	64 mm	
number of modular width units	1	
Environmental conditions		
ambient temperature / during operation		
• minimum	-5 °C	
• maximum	40 °C	
General Product Approval	Declaration of Conformity	other

[Confirmation](#)



[Miscellaneous](#)

other

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TE5802>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TE5802>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TE5802

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



