



SITOP PSE201U/BUFFER MODULE/10S

SITOP PSE201U buffer module Buffer time 100 ms to 10 s depending on load current *Ex approval no longer available*

Input	
supply voltage at DC rated value	24 V
voltage curve at input	DC
input voltage range	24 ... 28.8 V DC
Mains buffering	
design of the mains power cut bridging-connection	Backup time: with 40 A load current: 200 ms; with 20 A load current: 400 ms; with 10 A load current: 800 ms; with 5 A load current: 1.6 s. Reduces the backup time by 100 ms in combination with 6EP1 437-3BA10. Maximum backup time 100 ms in combination with 6EP1 336-2BA10 (load current 20 A).
Output	
formula for output voltage	$V_{in} - \text{approx. } 1 \text{ V}$
output current	40 A
<ul style="list-style-type: none"> rated value 	
Signaling	
display version	
<ul style="list-style-type: none"> for normal operation 	Green LED for "supply voltage > 20.5 V"
Interface	
product component PC interface	No
design of the interface	without
Safety	
galvanic isolation between input and output	Yes
operating resource protection class	Class III
protection class IP	IP20
Approvals	
certificate of suitability	Yes
<ul style="list-style-type: none"> CE marking as approval for USA 	UL-Listed (UL 508), File E197259; CSA (CSA C22.2 No. 14, CSA C22.2 No. 107.1)
<ul style="list-style-type: none"> C-Tick 	No
shipbuilding approval	ABS, DNV GL
EMC	
standard	
<ul style="list-style-type: none"> for emitted interference for interference immunity 	EN 55022 Class B EN 61000-6-2
environmental conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation during transport during storage 	-25 ... +70 °C; with natural convection -40 ... +85 °C -40 ... +85 °C

environmental category acc. to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
type of electrical connection <ul style="list-style-type: none"> • at input • at output • for control circuit and status message 	screw-type terminals +: 1 screw terminal for 0.5 ... 10 mm ² -: 1 screw terminal for 0.5 ... 10 mm ² -
width of the enclosure	70 mm
height of the enclosure	125 mm
depth of the enclosure	121 mm
required spacing <ul style="list-style-type: none"> • top • bottom • left • right 	50 mm 50 mm 0 mm 0 mm
net weight	1.2 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
MTBF at 40 °C	2 538 071 h
reference code acc. to IEC 81346-2	T
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

