SIEMENS

Data sheet 3VA9117-0HB20



side mounted motor operator 110-250V AC/DC accessory for: 3VA1 160

Model	
product brand name	SENTRON
product designation	Accessories
Product version	Lateral motorized operating mechanism
/oltage	
Type de tension pour la commande	AC/DC
 Rated control supply voltage Us at AC 50 Hz 	110 V
 Rated control supply voltage Us at AC 50 Hz 	230 V
 Rated control supply voltage Us at AC 60 Hz 	110 V
Rated control supply voltage Us at AC 60 Hz	230 V
Rated operational power	250 V·A
Mechanical Design	
Rated control supply voltage Us with DC	250 V
Height	149 mm
Width	78 mm
depth	93.8 mm
net weight	860 g
connectable conductor cross-section / solid	
• minimum	1.5 mm ²
maximum	2.5 mm ²
connectable conductor cross-section / finely stranded / with core end processing	
• minimum	1.5 mm ²
maximum	2.5 mm ²
connectable conductor cross-section / stranded	
• minimum	1.5 mm ²
maximum	2.5 mm ²
ambient temperature / during operation	
• minimum	-25 °C
maximum	70 °C
ambient temperature / during storage	
• minimum	-40 +80
maximum	
tightening torque	
• minimum	0.36 N·m
maximum	0.44 N·m

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9117-0HB20

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3VA9117-0HB20

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9117-0HB20


CAx-Online-Generator

http://www.siemens.com/cax

Tender specifications

http://www.siemens.com/specifications





last modified:

4/29/2021