

fixed-mounted molded case circuit breaker frame 1600; with RTC and 4AUX trip alarm switch S24; Icu "M" Icu=55kA @ 415V, 4-pole, left ETU350, LSI, In=1000A rotary coding switch Ir=400...1000A Isd=1...10xIn, li=1.5...15xIn N conductor protec. adjustable OFF, 50%, 100%, 200% nut keeper kit No communication connection, no measurement function Manual operating mechanism of the spring energy store With mechanical calling without 2nd auxiliary release without 1st auxiliary release

Model	
product brand name	SENTRON
product designation	Molded case circuit breaker
design of the product	MCCB
design of the actuating element	spring actuator
type of the driving mechanism	without motor drive
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU350
General technical data	
number of poles	4
size of the circuit-breaker	1600 A
mechanical service life (switching cycles) / typical	1 000
circuit-breaker / Design	3VA2
Voltage	
insulation voltage / rated value	1 000 V
operating voltage / at AC / at 50/60 Hz / rated value	690 V
protection class IP	IP20
protection class IP / on the front	IP20
protection function of the overcurrent release	LSI
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	30 W
Current	
continuous current / rated value	1 000 A
adjustable current response value current	
• of the current-dependent overload release / full-scale value	1 000 A
• of instantaneous short-circuit trip unit / minimum	1 500 A
• of instantaneous short-circuit trip unit / maximum	15 000 A
short-time withstand current (Icw)	
• limited to 1 s / rated value	20 kA
• at AC / at 415 V / limited to 0.5 s / rated value	20 kA
Main circuit	
operational current	
• at 40 °C / rated value	1 000 A
• at 50 °C / rated value	1 000 A
• at 55 °C / rated value	971 A
• at 60 °C / rated value	942 A
• at 65 °C / rated value	885 A
• at 70 °C / rated value	827 A
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	4
Suitability	
suitability for use	system protection
Adjustable parameters	

adjustable current response value current			
• of the short-time delayed short-circuit release / initial value	1 000 A		
• of the short-time delayed short-circuit release / full-scale value	10 000 A		
adjustable current response value current / of the current-dependent overload release / initial value	400 A		
product component			
• trip indicator	Yes		
• voltage trigger	No		
• undervoltage release	No		
product extension / optional / motor drive	Yes		
<b>Product function</b>			
product function			
• grounding protection	No		
<b>Display and operation</b>			
display version	Without display		
<b>Short circuit</b>			
breaking capacity operating short-circuit current (Ics)			
• at 415 V / rated value	55 kA		
• at 500 V / rated value	36 kA		
• at 690 V / rated value	25 kA		
breaking capacity maximum short-circuit current (Icu)			
• at 415 V / rated value	55 kA		
• at 440 V / rated value	55 kA		
• at 500 V / rated value	36 kA		
• at 690 V / rated value	25 kA		
<b>Connections</b>			
arrangement of electrical connectors / for main current circuit	Main connection on front side		
type of electrical connection / for main current circuit	busbar connection		
<b>Mechanical Design</b>			
height	296 mm		
width	280 mm		
depth	183 mm		
fastening method	fixed mounting		
net weight	16 kg		
<b>Environmental conditions</b>			
ambient temperature / during operation			
• minimum	-25 °C		
• maximum	70 °C		
ambient temperature / during storage			
• minimum	-40 °C		
• maximum	70 °C		
<b>Certificates</b>			
reference code			
• acc. to DIN EN 61346-2	Q		
• acc. to IEC 81346-2	Q		
<b>General Product Approval</b>	<b>EMC</b>	<b>Declaration of Conformity</b>	<b>Test Certificates</b>



[Miscellaneous](#)



[Miscellaneous](#)

other

Dangerous Good

#### Further information

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2710-1AC13-0AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2710-1AC13-0AA0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2710-1AC13-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2710-1AC13-0AA0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

# SIEMENS



last modified:

3/16/2020