

fixed-mounted molded case circuit breaker w. handle frame 1600; 4AUX and trip alarm switch S24; Icu "H" Icu=85kA @ 415V, 4-pole, left ETU320, LI, In=1250A rotary coding switch Ir=500...1250A li=1.5...15 x In N conductor protec. adjustable OFF, 50%, 100%, 200% nut keeper kit No communication connection, no measurement function Without additional alarm switch assembly With mechanical calling without 2nd auxiliary release without 1st auxiliary release

Model	
product brand name	SENTRON
product designation	Molded case circuit breaker
design of the product	MCCB
design of the actuating element	toggel handle actuator
type of the driving mechanism	manual operating mechanism
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU320
General technical data	
number of poles	4
size of the circuit-breaker	1600 A
mechanical service life (switching cycles) / typical	1 000
circuit-breaker / Design	3VA2
Voltage	
insulation voltage / rated value	1 000 V
operating voltage / at AC / at 50/60 Hz / rated value	690 V
protection class IP	IP20
protection class IP / on the front	IP20
protection function of the overcurrent release	LI
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	47 W
Current	
continuous current / rated value	1 250 A
adjustable current response value current	
• of the current-dependent overload release / full-scale value	1 250 A
• of instantaneous short-circuit trip unit / initial value	1 875 A
• of instantaneous short-circuit trip unit / full-scale value	18 750 A
short-time withstand current (Icw)	
• limited to 1 s / rated value	20 kA
• at AC / at 415 V / limited to 0.5 s / rated value	20 kA
Main circuit	
operational current	
• at 40 °C / rated value	1 250 A
• at 50 °C / rated value	1 250 A
• at 55 °C / rated value	1 240 A
• at 60 °C / rated value	1 182 A
• at 65 °C / rated value	1 122 A
• at 70 °C / rated value	1 057 A
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	4
Suitability	
suitability for use	system protection

Adjustable parameters				
adjustable current response value current / of the current-dependent overload release / initial value	500 A			
product component				
• trip indicator	Yes			
• voltage trigger	No			
• undervoltage release	No			
product extension / optional / motor drive	No			
Product function				
product function				
• grounding protection	No			
Display and operation				
display version	Without display			
Short circuit				
breaking capacity operating short-circuit current (Ics)				
• at 415 V / rated value	85 kA			
• at 500 V / rated value	55 kA			
• at 690 V / rated value	36 kA			
breaking capacity maximum short-circuit current (Icu)				
• at 415 V / rated value	85 kA			
• at 440 V / rated value	85 kA			
• at 500 V / rated value	55 kA			
• at 690 V / rated value	36 kA			
Connections				
arrangement of electrical connectors / for main current circuit	Main connection on front side			
type of electrical connection / for main current circuit	busbar connection			
Mechanical Design				
height	296 mm			
width	280 mm			
depth	183 mm			
fastening method	fixed mounting			
net weight	16 kg			
Environmental conditions				
ambient temperature / during operation				
• minimum	-25 °C			
• maximum	70 °C			
ambient temperature / during storage				
• minimum	-40 °C			
• maximum	70 °C			
Certificates				
reference code				
• acc. to DIN EN 61346-2	Q			
• acc. to IEC 81346-2	Q			
General Product Approval		EMC	Declaration of Conformity	Test Certificates



[Miscellaneous](#)



[Miscellaneous](#)

other

Dangerous Good

[Manufacturer Declaration](#)

[Miscellaneous](#)

[Miscellaneous](#)

[Dangerous Goods Information](#)

Further information

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2712-6AB13-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2712-6AB13-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2712-6AB13-0AA0

Tender specifications

<http://www.siemens.com/specifications>



last modified:

3/16/2020 