

SIMATIC S7-400H, Synchronization module V6 for patch cable to 10 m



Input current	
Current consumption, max.	220 mA
Power loss	
Power loss, typ.	0.77 W
Dimensions	
Width	13 mm
Height	14 mm
Depth	58 mm
Weights	
Weight, approx.	14 g
Classifications	

	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates
General Product Approval



[Miscellaneous](#)



[KC](#)



For use in hazardous locations



IECEEx



ATEX

[FM](#)



CCC



IECEEx



ATEX

For use in hazard-
ous locations

Marine / Shipping

[Type Examination Cer-
tificate](#)



ABS



BUREAU
VERITAS



DNV



LRS

[NK / Nippon Kaiji Ky-
okai](#)

Marine / Shipping

Environment



RINA

[CCS \(China Classifica-
tion Society\)](#)



last modified:

4/30/2025