



SIMATIC S7-1500, digital output module, DQ 64xDC 24V/0.3A BA, 64 channels in groups of 16, 2 A per group at 60 °C, sinking output, 35 mm wide, the module supports the safety-oriented shutdown of load groups up to SILCL2 acc. to EN 62061:2005 + A2:2015, and Category 3 / PL d according to EN ISO 13849-1:2015. cables and terminal blocks to be ordered separately as accessories

General information	
Product type designation	DQ 64x24VDC/0.3A BA
HW functional status	From FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	No
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V16 with HSP 0319 / V17
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	V2.35 / -
Operating mode	
<ul style="list-style-type: none"> <li>DQ</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DQ with energy-saving function</li> </ul>	No
<ul style="list-style-type: none"> <li>PWM</li> </ul>	No
<ul style="list-style-type: none"> <li>Cam control (switching at comparison values)</li> </ul>	No
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	No
<ul style="list-style-type: none"> <li>MSO</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Integrated operating cycle counter</li> </ul>	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes; through internal protection with 7 A per group
external protection for power supply lines (recommendation)	24 V DC/6 A miniature circuit breaker with type B tripping characteristic
Input current	
Current consumption, max.	90 mA; without load
Output voltage	
Rated value (DC)	24 V
Power	
Power available from the backplane bus	0.6 W
Power loss	
Power loss, typ.	3.5 W

Digital outputs	
Type of digital output	Transistor
Number of digital outputs	64
Current-sinking	No
Current-sourcing	Yes
Digital outputs, parameterizable	No
Short-circuit protection	Yes
Limitation of inductive shutdown voltage to	L+ (-53 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	0.3 A
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	5 W
Load resistance range	
<ul style="list-style-type: none"> <li>lower limit</li> </ul>	80 Ω
<ul style="list-style-type: none"> <li>upper limit</li> </ul>	10 kΩ
Output voltage	
<ul style="list-style-type: none"> <li>for signal "1", min.</li> </ul>	L+ (-0.8 V)
Output current	
<ul style="list-style-type: none"> <li>for signal "1" rated value</li> </ul>	0.3 A
<ul style="list-style-type: none"> <li>for signal "1" permissible range, max.</li> </ul>	0.3 A
<ul style="list-style-type: none"> <li>for signal "0" residual current, max.</li> </ul>	0.5 mA
Output delay with resistive load	
<ul style="list-style-type: none"> <li>"0" to "1", max.</li> </ul>	100 μs
<ul style="list-style-type: none"> <li>"1" to "0", max.</li> </ul>	500 μs
Parallel switching of two outputs	
<ul style="list-style-type: none"> <li>for logic links</li> </ul>	Yes
<ul style="list-style-type: none"> <li>for uprating</li> </ul>	No
<ul style="list-style-type: none"> <li>for redundant control of a load</li> </ul>	Yes
Switching frequency	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	100 Hz
<ul style="list-style-type: none"> <li>with inductive load, max.</li> </ul>	0.5 Hz; According to IEC 60947-5-1, DC-13
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	10 Hz
Total current of the outputs	
<ul style="list-style-type: none"> <li>Current per channel, max.</li> </ul>	0.3 A
<ul style="list-style-type: none"> <li>Current per group, max.</li> </ul>	2 A
<ul style="list-style-type: none"> <li>Current per module, max.</li> </ul>	8 A
Total current of the outputs (per module)	
horizontal installation	
<ul style="list-style-type: none"> <li>— up to 60 °C, max.</li> </ul>	8 A
vertical installation	
<ul style="list-style-type: none"> <li>— up to 40 °C, max.</li> </ul>	8 A
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Substitute values connectable	No
Alarms	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	No
<ul style="list-style-type: none"> <li>Maintenance interrupt</li> </ul>	No
Diagnoses	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> </ul>	No
<ul style="list-style-type: none"> <li>Wire-break</li> </ul>	No
<ul style="list-style-type: none"> <li>Short-circuit</li> </ul>	No
<ul style="list-style-type: none"> <li>Group error</li> </ul>	No
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>RUN LED</li> </ul>	Yes; green LED
<ul style="list-style-type: none"> <li>ERROR LED</li> </ul>	Yes; red LED

<ul style="list-style-type: none"> <li>• MAINT LED</li> <li>• Monitoring of the supply voltage (PWR-LED)</li> <li>• Channel status display</li> <li>• for channel diagnostics</li> <li>• for module diagnostics</li> </ul>	No Yes; via SIMATIC TOP connect connection module Yes; via SIMATIC TOP connect connection module No No
<b>Potential separation</b>	
Potential separation channels	
<ul style="list-style-type: none"> <li>• between the channels</li> <li>• between the channels, in groups of</li> <li>• between the channels and backplane bus</li> </ul>	No 16; 32 when using SIMATIC TOP connect connection module Yes
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Standards, approvals, certificates</b>	
Suitable for safety functions	No
Suitable for safety-related tripping of standard modules	Yes; From FS01
Highest safety class achievable for safety-related tripping of standard modules	
<ul style="list-style-type: none"> <li>• Performance level according to ISO 13849-1</li> <li>• Category according to ISO 13849-1</li> <li>• SILCL according to IEC 62061</li> </ul>	PL d Cat. 3 SILCL 2
<b>Ambient conditions</b>	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>	-30 °C 60 °C -30 °C 40 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> </ul>	5 000 m
<b>Dimensions</b>	
Width	35 mm
Height	147 mm
Depth	129 mm
<b>Weights</b>	
Weight, approx.	270 g
<b>Other</b>	
Note:	Please order cable and connection modules separately
<b>last modified:</b>	2/8/2021 