



SIMATIC ET 200SP, BusAdapter: BA SCRJ/FC, media converter FOC-CU  
1x SCRJ FO connection and, 1x FastConnect (FC) connection

General information	
Product type designation	BA SCRJ/FC
HW functional status	from FS04
Interfaces	
Number of PROFINET interfaces	1; 2 ports (SCRJ + FC)
Supports protocol for PROFINET IO	
<ul style="list-style-type: none"> <li>Number of FC (FastConnect) connections</li> <li>Number of SCRJ ports</li> <li>Number of LC ports</li> </ul>	1 1 0
Cable length	
<ul style="list-style-type: none"> <li>— PCF</li> <li>— Plastic FOC (POF)</li> <li>— PCF-GI</li> <li>— Cu conductors</li> </ul>	100 m 50 m 250 m 100 m
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-25 °C 60 °C -25 °C 50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>	2 000 m; On request: Installation altitudes greater than 2 000 m
Dimensions	
Width	20 mm
Height	69.5 mm
Depth	59 mm
Weights	
Weight, approx.	50 g
last modified:	3/3/2021