

SIMATIC S7, IF964-DP Interface module DP master for S7-400



### Input current

Current consumption, max.	150 mA; Current consumption from S7-400 bus: The module uses no current at 24 V, it provides this voltage only at the DP interface. Total current consumption of the components connected to the DP interface, but maximum 150 mA. Current carrying capacity of the isolated 5 V (P5ext) maximum 90 mA, current carrying capacity of the 24 V maximum 150 mA.
---------------------------	---

### Power loss

Power loss, typ.	1 W
------------------	-----

### Interfaces

#### PROFIBUS DP

- Cable length, max. 1 200 m; At 9.6 kbit/s: max. 1 200 m; at 12 Mbit/s: max. 100 m

### 1. Interface

Isolated	Yes
----------	-----

Protocols	
-----------	--

- PROFIBUS DP master Yes; Default setting
- PROFIBUS DP slave Yes

#### PROFIBUS DP master

- Transmission rate, max. 12 Mbit/s
- Number of DP slaves, max. 125; depending on the CPU used

#### Services

- PG/OP communication Yes
- Equidistance Yes
- SYNC/FREEZE Yes
- Direct data exchange (slave-to-slave communication) Yes

#### Address area

- Inputs, max. device-dependent
- Outputs, max. device-dependent

#### User data per DP slave

- Inputs, max. 244 byte
- Outputs, max. 244 byte

### Communication functions

Number of connections	
-----------------------	--

- overall device-dependent

### Dimensions

Width	26 mm
-------	-------

Height	54 mm
--------	-------

Depth	130 mm
<b>Weights</b>	
Weight, approx.	65 g
last modified:	7/1/2021 