

SCALANCE XR528-6M; managed IE switch; 19" rack; 4x 1000/10000 Mbit/s SFP+; 6x 100/1000 Mbit/s 4-port media modules, electrical, electrical PoE or optical; LED diagnostics; error signaling contact; Select/set pushbutton, PROFINET IO device, network management, integrated redundancy manager; office features (RSTP, VLAN, IGMP, ...); C-plug in scope of delivery Layer 3 integrated; ports at the back



<b>product type designation</b>	<b>SCALANCE XR528-6M</b>
<b>transfer rate</b>	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10 Gbit/s
<b>interfaces / for communication / integrated</b>	
number of electrical connections	
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> <li>for Power-over-Ethernet / for network components or terminal equipment</li> </ul>	RJ45 12
number of electrical connections	
<ul style="list-style-type: none"> <li>for SFP+</li> </ul>	4
<b>interfaces / for communication / plug-in</b>	
number of 100 Mbit/s ST(BFOC) ports	
<ul style="list-style-type: none"> <li>for multimode</li> <li>for single mode (LD)</li> </ul>	24 24
number of 1000 Mbit/s SC ports	
<ul style="list-style-type: none"> <li>for multimode</li> <li>for single mode (LD)</li> </ul>	24 24
number of electrical connections	
<ul style="list-style-type: none"> <li>for SFP</li> <li>for SFP+</li> </ul>	4 4
<b>interfaces / other</b>	
number of electrical connections	
<ul style="list-style-type: none"> <li>for operator console</li> <li>for management purposes</li> <li>for signaling contact</li> <li>for media module</li> <li>for power supply</li> </ul>	1 1 1 6 1
type of electrical connection	
<ul style="list-style-type: none"> <li>for operator console</li> <li>for management purposes</li> <li>for signaling contact</li> <li>for power supply</li> </ul>	RJ11 RJ45 2-pole terminal block 4-pole terminal block
design of the removable storage	
<ul style="list-style-type: none"> <li>C-PLUG/KEY-PLUG</li> </ul>	Yes
product feature / hot-swappable interface modules	Yes
<b>signal inputs/outputs</b>	
operating voltage / of the signaling contacts	

<ul style="list-style-type: none"> <li>• at DC / rated value</li> </ul>	24 V
operational current / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / maximum</li> </ul>	0.1 A
<b>supply voltage, current consumption, power loss</b>	
type of voltage supply / redundant power supply unit	No
supplied active power / of PSE / with PoE	
<ul style="list-style-type: none"> <li>• per port / maximum</li> </ul>	30 W
<ul style="list-style-type: none"> <li>• total / maximum</li> </ul>	180 W
<b>type of voltage / 1 / of the supply voltage</b>	DC
<ul style="list-style-type: none"> <li>• supply voltage / 1 / rated value</li> </ul>	24 V
<ul style="list-style-type: none"> <li>• power loss [W] / 1 / rated value</li> </ul>	22 W
<ul style="list-style-type: none"> <li>• supply voltage / 1 / rated value</li> </ul>	19.2 ... 28.8 V
<ul style="list-style-type: none"> <li>• consumed current / 1 / maximum</li> </ul>	11.5 A
<ul style="list-style-type: none"> <li>• type of electrical connection / 1 / for power supply</li> </ul>	4-pole terminal block
<ul style="list-style-type: none"> <li>• product component / 1 / fusing at power supply input</li> </ul>	Yes
<b>ambient conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	0 ... 60 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>• note</li> </ul>	Operation with integral fan, replaceable
relative humidity	
<ul style="list-style-type: none"> <li>• at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP20
<b>design, dimensions and weights</b>	
design	19" rack
number of modular height units / relating to 19-inch cabinet	2
width	449 mm
height	87.2 mm
depth	305 mm
net weight	10 kg
fastening method	
<ul style="list-style-type: none"> <li>• 19-inch installation</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• 35 mm top hat DIN rail mounting</li> </ul>	No
<ul style="list-style-type: none"> <li>• wall mounting</li> </ul>	No
<ul style="list-style-type: none"> <li>• S7-300 rail mounting</li> </ul>	No
<ul style="list-style-type: none"> <li>• S7-1500 rail mounting</li> </ul>	No
type of cable outlet	Cable outlet at rear
<b>product features, product functions, product components / general</b>	
cascading in cases of star topology	any (depending only on signal propagation time)
<b>product functions / management, configuration, engineering</b>	
product function	
<ul style="list-style-type: none"> <li>• CLI</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• web-based management</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• MIB support</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TRAPs via email</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• configuration with STEP 7</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RMON</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• port mirroring</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• multiport mirroring</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• CoS</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• PROFINET IO diagnosis</li> </ul>	Yes
PROFINET conformity class	B
product function / switch-managed	Yes
telegram length / for Ethernet / maximum	9216 byte
protocol / is supported	

• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	Yes
• GMRP	Yes
• DCP	Yes
• LLDP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher level designation/location designation	Yes
<b>product functions / diagnostics</b>	
product function	
• port diagnostics	Yes
• statistics Packet Size	Yes
• statistics packet type	Yes
• error statistics	Yes
• SysLog	Yes
<b>product functions / VLAN</b>	
product function	
• VLAN - port based	Yes
• VLAN - protocol-based	Yes
• VLAN - IP-based	Yes
• VLAN dynamic	Yes
number of VLANs / maximum	255
number of VLANs - dynamic / maximum	255
protocol / is supported / GVRP	Yes
<b>product functions / DHCP</b>	
product function	
• DHCP client	Yes
• DHCP Option 82	Yes
• DHCP Option 66	Yes
• DHCP Option 67	Yes
<b>product functions / routing</b>	
service / routing / note	IP routing integrated
product function	
• static IP routing	Yes
• static IP routing IPv6	Yes
• dynamic IP routing	Yes
• dynamic IP routing IPv6	Yes
protocol / is supported	
• RIPv2	Yes
• RIPv6 for IPv6	Yes
• OSPFv2	Yes
• OSPFv3 for IPv6	Yes
• VRRP	Yes
• VRRP for IPv6	Yes
<b>product functions / redundancy</b>	
product function	
• ring redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• high speed redundancy protocol (HRP) with redundancy manager	Yes

<ul style="list-style-type: none"> <li>• high speed redundancy protocol (HRP) with standby redundancy</li> </ul>	Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
<ul style="list-style-type: none"> <li>• media redundancy protocol (MRP) with redundancy manager</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Media Redundancy Protocol Interconnection (MRP-I)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• redundancy procedure STP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• redundancy procedure RSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• redundancy procedure RSTP+</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• redundancy procedure MSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• passive listening</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• LACP</li> </ul>	Yes
<b>product functions / security</b>	
product function	
<ul style="list-style-type: none"> <li>• ACL - MAC-based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• ACL - port/MAC-based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.1x (radius)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• broadcast/multicast/unicast limiter</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• broadcast blocking</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• SSH</li> </ul>	Yes
<b>product functions / time</b>	
product function	
<ul style="list-style-type: none"> <li>• SICLOCK support</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• NTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNTP</li> </ul>	Yes
type of time synchronization	IEEE 1588
<b>standards, specifications, approvals</b>	
standard	
<ul style="list-style-type: none"> <li>• for FM</li> </ul>	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
<ul style="list-style-type: none"> <li>• for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1-03
<ul style="list-style-type: none"> <li>• for emitted interference</li> </ul>	EN 61000-6-4 (Class A)
<ul style="list-style-type: none"> <li>• for interference immunity</li> </ul>	EN 61000-6-2
<b>standards, specifications, approvals / CE</b>	
certificate of suitability / CE marking	Yes
<b>standards, specifications, approvals / hazardous environments</b>	
standard / for hazardous zone	EN 60079-0: 2009, EN60079-15: 2010, II 3 G Ex nA IIC T4 Gc, KEMA 07 ATEX 0145 X
<ul style="list-style-type: none"> <li>• from CSA and UL</li> </ul>	ISA 12.12.01-2012 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
certificate of suitability	
<ul style="list-style-type: none"> <li>• CCC / for hazardous zone according to GB standard</li> </ul>	Yes
<b>standards, specifications, approvals / other</b>	
certificate of suitability	EN 61000-6-2, EN 61000-6-4
<ul style="list-style-type: none"> <li>• C-Tick</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• KC approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• E1 approval</li> </ul>	No
<ul style="list-style-type: none"> <li>• E1 approval</li> </ul>	No
<b>standards, specifications, approvals / marine classification</b>	
Marine classification association	
<ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• French marine classification society (BV)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DNV GL</li> </ul>	Yes

- |  |     |
|--|-----|
| • Lloyds Register of Shipping (LRS)            | Yes |
| • Nippon Kaiji Kyokai (NK)                     | Yes |
| • Polski Rejestr Statkow (PRS)                 | Yes |
| • Royal Institution of Naval Architects (RINA) | Yes |

#### further information / internet-Links

##### Internet-Link

- |   |   |
|---|---|
| • to web page: selection aid TIA Selection Tool | <a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>   |
| • to website: Industrial communication          | <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>                 |
| • to website: Industry Mall                     | <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>                   |
| • to website: Information and Download Center   | <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> |
| • to website: Image database                    | <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>             |
| • to website: CAX-Download-Manager              | <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>                                 |
| • to website: Industry Online Support           | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>             |

#### security information

##### security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

7/1/2021 