

SCALANCE XR526-8C; managed IE switch; Layer 3 integrated; power supply 230 V AC; 24x 10/100/1000 Mbit/s RJ45; 8x 100/1000 Mbit/s SFP Combo; 2x 10 Gbit/S SFP+; in total 26 ports can be used; error signaling contact; select/set button; PROFINET IO device; redundancy functions; office features (RSTP, VLAN, IGMP, ...); C-plug in scope of delivery



|                                                                             |                                               |
|-----------------------------------------------------------------------------|-----------------------------------------------|
| <b>product type designation</b>                                             | <b>SCALANCE XR526-8C</b>                      |
| <b>transfer rate</b>                                                        |                                               |
| transfer rate                                                               | 10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10 Gbit/s |
| <b>interfaces / for communication / integrated</b>                          |                                               |
| number of electrical connections                                            |                                               |
| • for network components or terminal equipment                              | 24; RJ45                                      |
| number of 100 Mbit/s ST(BFOC) ports                                         |                                               |
| • for multimode                                                             | 0                                             |
| number of 100 Mbit/s SC ports                                               |                                               |
| • for multimode                                                             | 0                                             |
| number of 1000 Mbit/s LC ports                                              |                                               |
| • for multimode                                                             | 8                                             |
| • for single mode (LD)                                                      | 8                                             |
| number of electrical connections                                            |                                               |
| • for SFP                                                                   | 8                                             |
| • for SFP+                                                                  | 2                                             |
| number of combo ports / with RJ45 interface for optical plug-in transceiver | 8                                             |
| <b>interfaces / for communication / plug-in</b>                             |                                               |
| number of electrical connections                                            |                                               |
| • for SFP                                                                   | 10                                            |
| • for SFP+                                                                  | 2                                             |
| <b>interfaces / other</b>                                                   |                                               |
| number of electrical connections                                            |                                               |
| • for operator console                                                      | 1                                             |
| • for management purposes                                                   | 1                                             |
| • for signaling contact                                                     | 1                                             |
| • for power supply                                                          | 1                                             |
| type of electrical connection                                               |                                               |
| • for operator console                                                      | RJ11                                          |
| • for management purposes                                                   | RJ45                                          |
| • for signaling contact                                                     | 2-pole terminal block                         |
| • for power supply                                                          | 4-pole terminal block                         |
| design of the removable storage                                             |                                               |
| • C-PLUG/KEY-PLUG                                                           | Yes                                           |
| product feature / hot-swappable interface modules                           | Yes                                           |
| <b>signal inputs/outputs</b>                                                |                                               |

|                                                                          |                                                 |
|--------------------------------------------------------------------------|-------------------------------------------------|
| operating voltage / of the signaling contacts<br>• at DC / rated value   | 24 V                                            |
| operational current / of the signaling contacts<br>• at DC / maximum     | 0.1 A                                           |
| <b>supply voltage, current consumption, power loss</b>                   |                                                 |
| product component / connection for redundant voltage supply              | Yes                                             |
| type of voltage supply / redundant power supply unit                     | No                                              |
| <b>type of voltage / 1 / of the supply voltage</b>                       |                                                 |
| • supply voltage / 1 / rated value                                       | 230 V                                           |
| • power loss [W] / 1 / rated value                                       | 36 W                                            |
| • supply voltage / 1 / rated value                                       | 90 ... 264 V                                    |
| • consumed current / 1 / maximum                                         | 1.5 A                                           |
| • type of electrical connection / 1 / for power supply                   | 4-pole terminal block                           |
| • product component / 1 / fusing at power supply input                   | Yes                                             |
| <b>ambient conditions</b>                                                |                                                 |
| ambient temperature                                                      |                                                 |
| • during operation                                                       | 0 ... 50 °C                                     |
| • during storage                                                         | -40 ... +85 °C                                  |
| • during transport                                                       | -40 ... +85 °C                                  |
| relative humidity                                                        |                                                 |
| • at 25 °C / without condensation / during operation / maximum           | 95 %                                            |
| protection class IP                                                      | IP20                                            |
| <b>design, dimensions and weights</b>                                    |                                                 |
| design                                                                   | 19" rack                                        |
| number of modular height units / relating to 19-inch cabinet             | 1                                               |
| width                                                                    | 449 mm                                          |
| height                                                                   | 44 mm                                           |
| depth                                                                    | 305 mm                                          |
| net weight                                                               | 4.4 kg                                          |
| fastening method                                                         |                                                 |
| • 19-inch installation                                                   | Yes                                             |
| • 35 mm top hat DIN rail mounting                                        | No                                              |
| • wall mounting                                                          | No                                              |
| • S7-300 rail mounting                                                   | No                                              |
| • S7-1500 rail mounting                                                  | No                                              |
| type of cable outlet                                                     | Cable outlet at front                           |
| <b>product features, product functions, product components / general</b> |                                                 |
| cascading in cases of star topology                                      | any (depending only on signal propagation time) |
| <b>product functions / management, configuration, engineering</b>        |                                                 |
| product function                                                         |                                                 |
| • CLI                                                                    | Yes                                             |
| • web-based management                                                   | Yes                                             |
| • MIB support                                                            | Yes                                             |
| • TRAPs via email                                                        | Yes                                             |
| • configuration with STEP 7                                              | Yes                                             |
| • RMON                                                                   | Yes                                             |
| • port mirroring                                                         | Yes                                             |
| • multipoint mirroring                                                   | Yes                                             |
| • CoS                                                                    | Yes                                             |
| • PROFINET IO diagnosis                                                  | Yes                                             |
| PROFINET conformity class                                                | B                                               |
| product function / switch-managed                                        | Yes                                             |
| telegram length / for Ethernet / maximum                                 | 9216 byte                                       |
| protocol / is supported                                                  |                                                 |
| • Telnet                                                                 | Yes                                             |

|                                                                |                       |
|----------------------------------------------------------------|-----------------------|
| • HTTP                                                         | Yes                   |
| • HTTPS                                                        | Yes                   |
| • TFTP                                                         | Yes                   |
| • FTP                                                          | Yes                   |
| • BOOTP                                                        | Yes                   |
| • GMRP                                                         | Yes                   |
| • DCP                                                          | Yes                   |
| • LLDP                                                         | Yes                   |
| • SNMP v1                                                      | Yes                   |
| • SNMP v2                                                      | Yes                   |
| • SNMP v3                                                      | Yes                   |
| • IGMP (snooping/querier)                                      | Yes                   |
| identification & maintenance function                          |                       |
| • I&M0 - device-specific information                           | Yes                   |
| • I&M1 – higher level designation/location designation         | Yes                   |
| <b>product functions / diagnostics</b>                         |                       |
| product function                                               |                       |
| • port diagnostics                                             | Yes                   |
| • statistics Packet Size                                       | Yes                   |
| • statistics packet type                                       | Yes                   |
| • error statistics                                             | Yes                   |
| • SysLog                                                       | Yes                   |
| <b>product functions / VLAN</b>                                |                       |
| product function                                               |                       |
| • VLAN - port based                                            | Yes                   |
| • VLAN - protocol-based                                        | Yes                   |
| • VLAN - IP-based                                              | Yes                   |
| • VLAN dynamic                                                 | Yes                   |
| number of VLANs / maximum                                      | 255                   |
| number of VLANs - dynamic / maximum                            | 255                   |
| protocol / is supported / GVRP                                 | Yes                   |
| <b>product functions / DHCP</b>                                |                       |
| product function                                               |                       |
| • DHCP client                                                  | Yes                   |
| • DHCP Option 82                                               | Yes                   |
| • DHCP Option 66                                               | Yes                   |
| • DHCP Option 67                                               | Yes                   |
| <b>product functions / routing</b>                             |                       |
| service / routing / note                                       | IP routing integrated |
| product function                                               |                       |
| • static IP routing                                            | Yes                   |
| • static IP routing IPv6                                       | Yes                   |
| • dynamic IP routing                                           | Yes                   |
| • dynamic IP routing IPv6                                      | Yes                   |
| protocol / is supported                                        |                       |
| • RIPv2                                                        | Yes                   |
| • RIPnG for IPv6                                               | Yes                   |
| • OSPFv2                                                       | Yes                   |
| • OSPFv3 for IPv6                                              | Yes                   |
| • VRRP                                                         | Yes                   |
| • VRRP for IPv6                                                | Yes                   |
| <b>product functions / redundancy</b>                          |                       |
| product function                                               |                       |
| • ring redundancy                                              | Yes                   |
| • High Speed Redundancy Protocol (HRP)                         | Yes                   |
| • high speed redundancy protocol (HRP) with redundancy manager | Yes                   |
| • high speed redundancy protocol (HRP) with standby            | Yes                   |

|                                                                     |                                                                                                   |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| redundancy                                                          |                                                                                                   |
| protocol / is supported / Media Redundancy Protocol (MRP)           | Yes                                                                                               |
| product function                                                    |                                                                                                   |
| • media redundancy protocol (MRP) with redundancy manager           | Yes                                                                                               |
| • Media Redundancy Protocol Interconnection (MRP-I)                 | Yes                                                                                               |
| • redundancy procedure STP                                          | Yes                                                                                               |
| • redundancy procedure RSTP                                         | Yes                                                                                               |
| • redundancy procedure RSTP+                                        | Yes                                                                                               |
| • redundancy procedure MSTP                                         | Yes                                                                                               |
| • passive listening                                                 | Yes                                                                                               |
| protocol / is supported                                             |                                                                                                   |
| • LACP                                                              | Yes                                                                                               |
| <b>product functions / security</b>                                 |                                                                                                   |
| product function                                                    |                                                                                                   |
| • ACL - MAC-based                                                   | Yes                                                                                               |
| • ACL - port/MAC-based                                              | Yes                                                                                               |
| • IEEE 802.1x (radius)                                              | Yes                                                                                               |
| • broadcast/multicast/unicast limiter                               | Yes                                                                                               |
| • broadcast blocking                                                | Yes                                                                                               |
| protocol / is supported                                             |                                                                                                   |
| • SSH                                                               | Yes                                                                                               |
| <b>product functions / time</b>                                     |                                                                                                   |
| product function                                                    |                                                                                                   |
| • SICLOCK support                                                   | Yes                                                                                               |
| protocol / is supported                                             |                                                                                                   |
| • NTP                                                               | Yes                                                                                               |
| • SNTP                                                              | Yes                                                                                               |
| <b>standards, specifications, approvals</b>                         |                                                                                                   |
| standard                                                            |                                                                                                   |
| • for safety / from CSA and UL                                      | available soon                                                                                    |
| • for emitted interference                                          | EN 61000-6-4 (Class A)                                                                            |
| • for interference immunity                                         | EN 61000-6-2                                                                                      |
| <b>standards, specifications, approvals / CE</b>                    |                                                                                                   |
| certificate of suitability / CE marking                             | Yes                                                                                               |
| <b>standards, specifications, approvals / other</b>                 |                                                                                                   |
| certificate of suitability                                          | EN 61000-6-2, EN 61000-6-4                                                                        |
| • C-Tick                                                            | Yes                                                                                               |
| • KC approval                                                       | Yes                                                                                               |
| • E1 approval                                                       | No                                                                                                |
| • E1 approval                                                       | No                                                                                                |
| <b>standards, specifications, approvals / marine classification</b> |                                                                                                   |
| Marine classification association                                   |                                                                                                   |
| • American Bureau of Shipping Europe Ltd. (ABS)                     | Yes                                                                                               |
| • French marine classification society (BV)                         | Yes                                                                                               |
| • DNV GL                                                            | Yes                                                                                               |
| • Korean Register of Shipping (KRS)                                 | Yes                                                                                               |
| • Lloyds Register of Shipping (LRS)                                 | Yes                                                                                               |
| • Nippon Kaiji Kyokai (NK)                                          | Yes                                                                                               |
| • Polski Rejestr Statkow (PRS)                                      | Yes                                                                                               |
| • Royal Institution of Naval Architects (RINA)                      | Yes                                                                                               |
| <b>further information / internet-Links</b>                         |                                                                                                   |
| Internet-Link                                                       |                                                                                                   |
| • to web page: selection aid TIA Selection Tool                     | <a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a> |
| • to website: Industrial communication                              | <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>               |
| • to website: Industry Mall                                         | <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>                 |

- to website: Information and Download Center
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/industry/infocenter>  
<http://automation.siemens.com/bilddb>  
<http://www.siemens.com/cax>  
<https://support.industry.siemens.com>

## security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

7/1/2021 