



SIMATIC IFP2400 V2 PRO, 24 multi-touch display (16:9) portrait format with 1080x1920 (portrait) pixels resolution, PRO upright support arm, with operator control, for 24 V DC, DisplayPort, can be placed up to 100 m away HDBaseT, USB on the rear side, standard design

General information	
Product type designation	IFP2400 PRO
Short designation	Flat Panel 24" PRO multi-touch ext.
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	23.8 in
Screen diagonal [cm]	60.47 cm
Display width	296 mm
Display height	527 mm
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216; 24 bit
Viewing angle	178° x 178°
Resolution (pixels)	
<ul style="list-style-type: none"> Image resolution 	1 080 x 1 920
<ul style="list-style-type: none"> Horizontal image resolution 	1 080 pixel
<ul style="list-style-type: none"> Vertical image resolution 	1 920 pixel
<ul style="list-style-type: none"> Pixel size, horizontal 	0.2745 mm
<ul style="list-style-type: none"> Pixel size, vertical 	0.2745 mm
General features	
<ul style="list-style-type: none"> Brightness/contrast 	250 cd/m ² / 1 000:1
<ul style="list-style-type: none"> Detachable from computer unit 	100 m; HDBaseT V2.0
<ul style="list-style-type: none"> Luminance 	250 cd/m ²
Backlighting	
<ul style="list-style-type: none"> Type of backlighting 	LED
<ul style="list-style-type: none"> MTBF backlighting (at 25 °C) 	50 000 h; At 25°C
<ul style="list-style-type: none"> Backlight dimmable 	Yes; 0-100 %
Control elements	
Control elements	multi-touch screen
Touch operation	
<ul style="list-style-type: none"> Design as multi-touch screen 	Yes; Projective-capacitive
<ul style="list-style-type: none"> Monitor keyboard 	Yes
Installation type/mounting	
Design	Support arm mounting
Support arm mounting	Yes; Suitable for support arm and extension components (please refer to manual)
Stand mounting	Yes
maximum permitted forward tilt angle from vertical	45°
maximum permitted backward tilt angle from vertical	45°

Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; PELV / SELV floating
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	1.5 A
Current consumption, max.	1.9 A
Starting current inrush I ² t	0.5 A ² ·s
Power loss	
Power loss, typ.	36 W
Power loss, max.	41 W
Interfaces	
Number of USB interfaces	2; USB 2.0 type A
USB on the rear	Yes; 2x onboard
Connection for keyboard/mouse	USB
Video interfaces	
<ul style="list-style-type: none"> • DisplayPort 	Yes; Display port V1.2
Touch interfaces	
<ul style="list-style-type: none"> • USB 	Yes
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP65
NEMA (front)	
<ul style="list-style-type: none"> • Enclosure Type 4 at the front 	Yes
<ul style="list-style-type: none"> • Enclosure Type 4x at the front 	Yes
Standards, approvals, certificates	
Certificate of suitability	hazardous zone 2/22; shipbuilding
CE mark	Yes
UL approval	Yes; cULus, cUL
cULus	Yes
FM approval	Available soon
RCM (formerly C-TICK)	Yes
EAC (formerly Gost-R)	Yes
EMC	CE, EN 55011, EN 61000-6-4, EN 61000-6-2
Marine approval	Available soon
Use in hazardous areas	
<ul style="list-style-type: none"> • ATEX Zone 2 	Yes; Available soon
<ul style="list-style-type: none"> • ATEX Zone 22 	Yes; Available soon
<ul style="list-style-type: none"> • IECEx Zone 2 	Yes; Available soon
<ul style="list-style-type: none"> • IECEx Zone 22 	Yes; Available soon
<ul style="list-style-type: none"> • cULus Class I Zone 2, Division 2 	Yes; Available soon
<ul style="list-style-type: none"> • FM Class I Division 2 	Yes; Available soon
Marine approval	
<ul style="list-style-type: none"> • Germanischer Lloyd (GL) 	Yes; In application process
<ul style="list-style-type: none"> • American Bureau of Shipping (ABS) 	Yes; In application process
<ul style="list-style-type: none"> • Bureau Veritas (BV) 	Yes; In application process
<ul style="list-style-type: none"> • Det Norske Veritas (DNV) 	Yes; In application process
<ul style="list-style-type: none"> • Lloyds Register of Shipping (LRS) 	Yes; In application process
<ul style="list-style-type: none"> • Nippon Kaiji Kyokai (Class NK) 	Yes; In application process
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. 	0 °C
<ul style="list-style-type: none"> • max. 	45 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> • min. 	-20 °C
<ul style="list-style-type: none"> • max. 	60 °C

Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 500 m
Relative humidity	
• Operation, max.	95 %; no condensation
Vibrations	
• Vibration load in operation	1 gn
• Vibration load during transport/storage	1 gn
Shock testing	
• Shock load during operation	15 gn
• shock acceleration during storage/transport	15 gn
Mechanics/material	
Enclosure material (front)	In standard design
• Aluminum	Yes
• Aluminum casting	Yes
• Glass	Yes; at front
Enclosure material (rear)	aluminum
Dimensions	
Width	361 mm
Height	583 mm; Without basic adapter
Depth	162.8 mm; Without basic adapter
Weights	
Weight (without packaging)	9.2 kg
Weight (with packaging)	11.2 kg
last modified:	1/18/2021 