## **SIEMENS**

## **Data sheet**

## 6ES7321-1FF10-0AA0



SIMATIC S7-300, Digital input SM 321, isolated, 8 DI, 120 V/230 V AC, 1x 40-pole, with single rooting/channel

Figure simila

Supply voltage	
Load voltage L1	
Rated value (AC)	230 V; 120/230 V AC; all load voltages must have the same phase.
Input current	
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	4.9 W
Digital inputs	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 60 °C, max.	8
vertical installation	
— up to 40 °C, max.	8
Input voltage	
<ul> <li>Type of input voltage</li> </ul>	AC
<ul><li>Rated value (AC)</li></ul>	120 V; 120/230 V AC (47 63 Hz)
● for signal "0"	0 to 40V
for signal "1"	79 to 264V
Input current	
for signal "1", typ.	7.5 mA; (120 V); 17.3 mA (230 V)
Input delay (for rated value of input voltage)	
for standard inputs	
<ul><li>parameterizable</li></ul>	No
— at "0" to "1", max.	25 ms
— at "1" to "0", max.	25 ms
Cable length	
• shielded, max.	1 000 m
unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
<ul> <li>permissible quiescent current (2-wire sensor), max.</li> </ul>	2 mA
Interrupts/diagnostics/status information	

Alarms	No
Diagnostics function	No
Alarms	
<ul> <li>Diagnostic alarm</li> </ul>	No
Hardware interrupt	No
Diagnostics indication LED	
<ul> <li>Group error SF (red)</li> </ul>	No
<ul> <li>Status indicator digital input (green)</li> </ul>	Yes
Potential separation	
Potential separation digital inputs	
<ul> <li>between the channels</li> </ul>	Yes
<ul> <li>between the channels, in groups of</li> </ul>	1
<ul> <li>between the channels and backplane bus</li> </ul>	Yes; Optocoupler
Isolation	
Isolation tested with	1 500 V AC
Connection method	
required front connector	40-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	240 g

last modified:

1/16/2021 🗗