

Connection box PN Basic for Mobile Panels (PROFINET)



General information	
Product function	
<ul style="list-style-type: none"> Location identifier 	Yes
FH technology	
Safety evaluation through direct wiring	
<ul style="list-style-type: none"> Reconnection with emergency stop circuit interruption 	Yes
<ul style="list-style-type: none"> Monitoring the STOP button 	No
Supply voltage	
Type of supply voltage	24 V DC
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.4 A
Power	
Active power input, typ.	10 W
Interfaces	
Interfaces/bus type	Ethernet
Number of industrial Ethernet interfaces	2; RJ45 not for interface boxes of mobile panels
Connection point identification	Yes
Industrial Ethernet	
<ul style="list-style-type: none"> Industrial Ethernet interface 	2x Fast Ethernet
<ul style="list-style-type: none"> Industrial Ethernet status LED 	6
Degree and class of protection	
IP degree of protection	IP65
Standards, approvals, certificates	
CE mark	Yes
CSA approval	No
UL approval	No
cULus	Yes
RCM (formerly C-TICK)	Yes
EAC (formerly Gost-R)	No
Marine approval	No
Use in hazardous areas	
<ul style="list-style-type: none"> ATEX Zone 2 	No
<ul style="list-style-type: none"> ATEX Zone 22 	No
<ul style="list-style-type: none"> FM Class I Division 2 	No

Ambient conditions	
Ambient temperature during operation	
Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Relative humidity	
• Operation, max.	85 %
Dimensions	
Width	230 mm
Height	120 mm
Depth	80 mm
Weights	
Weight (without packaging)	0.45 kg
Other	
free hotline	Yes
Usable in the following products	
• Product 1	6AV6645-0BA01-0AX0
• Product 2	6AV6645-0BB01-0AX0
• Product 3	6AV6645-0BC01-0AX0
• Product 4	6AV6645-0BE02-0AX0
• Product 5	6AV6645-0C*

last modified:

3/26/2021 