



Figure similar

SIMATIC S7-300, CP 340 Communications processor with RS232C interface (RS-232-C) incl. configuration package on CD

General information	
Product type designation	CP 340
Supply voltage	
Rated value (DC)	
• 24 V DC	No; Power supply via backplane bus 5V
Input current	
from backplane bus 5 V DC, max.	165 mA
Power loss	
Power loss, typ.	0.6 W
Power loss, max.	0.85 W
Interfaces	
Interfaces/bus type	RS 232C (V.24)
Number of interfaces	1; Isolated
Transmission rate, min.	2.4 kbit/s
Transmission rate, max.	19.2 kbit/s
Point-to-point connection	
• Cable length, max.	15 m
• supported printers	HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined
• Connector type	9-pin sub D connector
Integrated protocol driver	
— 3964 (R)	Yes
— ASCII	Yes
— RK 512	No
— customer-specific drivers reloadable	No
Telegram length, max.	
— 3964 (R)	1 024 byte
— ASCII	1 024 byte
Transmission speed, RS 232	
— with 3964 (R) protocol, max.	19.2 kbit/s
— with ASCII protocol, max.	9.6 kbit/s
— with printer driver, max.	9.6 kbit/s
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	

- min. -40 °C
- max. 70 °C

### Software

Block	
• FB length in RAM, max.	2 700 byte; Data communication, sending and receiving

### Connection method

Design of electrical connection for supply voltage	Over backplane bus
--	--------------------

### Dimensions

Width	40 mm
Height	125 mm
Depth	120 mm

### Weights

Weight, approx.	300 g
-----------------	-------

**last modified:** 2/26/2021 