6GK7377-1AA00-0AA0

Data sheet



Compact Switch Module CSM 377 Connection SIMATIC S7-300 and up to 3 further nodes to Industrial Ethernet with 10/100 Mbit/s unmanaged switch, 4 RJ45 ports, External 24 V DC power supply LED diagnostics, S7-300 module, incl. electron. Equipment Manual on CD-ROM

product type designation	SCALANCE CSM 377
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
 for network components or terminal equipment 	4
number of 100 Mbit/s SC ports	
for multimode	0
number of 1000 Mbit/s LC ports	
 for multimode 	0
for single mode (LD)	0
interfaces / other	
number of electrical connections	
for power supply	1
type of electrical connection	
 for power supply 	2-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / 1 / of the supply voltage	DC
supply voltage / 1 / rated value	24 V
power loss [W] / 1 / rated value	1.6 W
supply voltage / 1 / rated value	19.2 28.8 V
consumed current / 1 / maximum	0.07 A
 type of electrical connection / 1 / for power supply 	2-pole terminal block
 product component / 1 / fusing at power supply input 	Yes
ambient conditions	
ambient temperature	
during operation	0 60 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
relative humidity	
at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	SIMATIC S7-300 device design
width	40 mm
height	125 mm

depth	118 mm
net weight	0.2 kg
fastening method	
35 mm top hat DIN rail mounting	No
wall mounting	No
S7-300 rail mounting	Yes
S7-1500 rail mounting	No
product functions / management, configuration, engineering	
product function	יט
multiport mirroring	No
product function / switch-managed	No
product functions / redundancy	
product function	Yes
 Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	tes
Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T, CL.1, Zone 2, GP.
	IIC, T Ta
 for safety / from CSA and UL 	UL 508, CSA C22.2 No. 142
for emitted interference	EN 61000-6-4:2001
• for interference immunity	EN 61000-6-2:2001
MTBF	144 y
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environm	nents
standard / for hazardous zone	EN 60079-15, II 3 G Ex nA II T, KEMA 06 ATEX 0021 X
• from CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location)
certificate of suitability	of 1004 and of 2210 to (nazaraodo foodion)
CCC / for hazardous zone according to GB standard	Yes
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-2:2001, EN 61000-6-4:2001
C-Tick	
	Yes
KC approval	No
standards, specifications, approvals / marine classification	1
Marine classification association	
American Bureau of Shipping Europe Ltd. (ABS)	Yes
 French marine classification society (BV) 	Yes
Det Norske Veritas (DNV)	Yes
Germanische Lloyd (GL)	No
Lloyds Register of Shipping (LRS)	Yes
 Nippon Kaiji Kyokai (NK) 	Yes
 Polski Rejestr Statkow (PRS) 	No
Royal Institution of Naval Architects (RINA)	No
further information / internet-Links	
Internet-Link	
 to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
 to website: Industrial communication 	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security
•	functions that support the secure operation of plants, solutions,

machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

6/11/2021