

SiePortal

The integrated platform for your information, buying and ordering workflow – bringing together Industry Mall and Online Support.

6DR5125-0EG01-0AA0



Image similar

SIPART PS2 Smart, electropneumatic positioner, 4...20mA, HART, Ex/nEx, double-acting, aluminum enclosure, flameproof (Ex d), for pneumatic linear and part-turn actuators, Non-contacting (wear-free) position detection (NCS), Not in combination with pressure sensor option P01/P02, Standard Type of protection (Ex): Flameproof enclosure (Ex d), Dust ignition protection by enclosure (Ex t), Connection thread el.: M20x1,5 / pneu.: G 1/4 Without limit monitor, Analog Output Module (AOM), analog position feedback 4 ... 20 mA, Isolating power supply SITRANS I100 separately orderable (7NG4124-1AA00). . Brief instructions English / German / Chinese, Standard / Fail-Safe - Depressurizing the actuator in case of failure of electrical auxiliary power (single acting only), Without Manometer block / Venting gauge block / Booster.

List Price	Show prices
Customer Price	Show prices
Additional Services	<p>For this product we can offer Services like Spare Part Delivery/Repair/Exchange, You have currently no rights to enter the Service Web Shop for that.</p> <p>For further information & to order this service, please contact your local Spares&Repair Partner</p> <p>For this product we can offer extended warranty contracts</p> <p>EEO (material exchange for a single product)</p> <p>OEM RSC (Repair Service Contract for a whole machine)</p> <p>For further information & to order these services, please contact your local Siemens Service Partner</p>
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	6DR5125-0EG01-0AA0
Product Description	SIPART PS2 Smart, electropneumatic positioner, 4...20mA, HART, Ex/nEx, double-acting, aluminum enclosure, flameproof (Ex d), for pneumatic linear and part-turn actuators, Non-contacting (wear-free) position detection (NCS), Not in combination with pressure sensor option P01/P02, Standard Type of protection (Ex): Flameproof enclosure (Ex d), Dust ignition protection by enclosure (Ex t), Connection thread el.: M20x1,5 / pneu.: G 1/4 Without limit monitor, Analog Output Module (AOM), analog position feedback 4 ... 20 mA, Isolating power supply SITRANS I100 separately orderable (7NG4124-1AA00). . Brief instructions English / German / Chinese, Standard / Fail-Safe - Depressurizing the actuator in case of failure of electrical auxiliary power (single acting only), Without Manometer block / Venting gauge block / Booster.
Product family	SIPART PS2
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group / Headquarter Price Group	8V1
List Price	Show prices
Customer Price	Show prices
Metal Factor	None

Delivery information

Export Control Regulations	ECCN : N / AL : N
Estimated dispatch time (Working Days)	10 Day/Days
Net Weight (kg)	5.200 Kg
Package size unit of measure	Not available
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	Not available
UPC	Not available
Commodity Code	90328100
LKZ_FDB/ CatalogID	FI01-5
Product Group	4759
Group Code	R3P2
Country of origin	Germany
Compliance with the substance restrictions according to RoHS directive	Since: 31/12/16
Product class	C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

Classifications

	Version	Classification
eClass	12	27-22-04-01
eClass	14	27-22-04-01
eClass	7.1	27-22-04-01
eClass	8	27-22-04-01
eClass	9	27-22-04-01
eClass	9.1	27-22-04-01
UNSPSC	15	32-15-17-03

