SIEMENS

Data sheet

6GK7542-5FX00-0XE0

product type designation



CP 1542-5

Communications processor CP 1542-5 for connection of SIMATIC S7-1500 to PROFIBUS DP, DPV1 master or DP slave, S7 and PG/OP communication, time-of-day synchronization, diagnostics, reduced quantity structure

transfer rate	
transfer rate	
 at the 1st interface / acc. to PROFIBUS 	9.6 kbit/s 12 Mbit/s
interfaces	
number of interfaces / acc. to Industrial Ethernet	0
number of electrical connections	
 at the 1st interface / acc. to PROFIBUS 	1
type of electrical connection	
 at the 1st interface / acc. to PROFIBUS 	9-pin Sub-D socket (RS485)
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	15 V
relative symmetrical tolerance / at DC	
● at 15 V	3 %
consumed current	
• from backplane bus / at DC / at 15 V / typical	0.1 A
power loss [W]	1.5 W
ambient conditions	
ambient temperature	
 for vertical installation / during operation 	0 40 °C
 for horizontally arranged busbars / during operation 	0 60 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1500 single width
width	35 mm
height	142 mm
depth	129 mm
net weight	0.27 kg
fastening method	
S7-1500 rail mounting	Yes
product features, product functions, product components	/ general

number of units	
• per CPU / maximum	8
• note	depending on CPU type
performance data / PROFIBUS DP	
service / as DP master	
• DPV1	Yes
number of DP slaves	
on DP master / operable	32
data volume	
 of the address range of the inputs / as DP master / total 	2048 byte
 of the address range of the outputs / as DP master / total 	2048 byte
 of the address range of the inputs / per DP slave 	244 byte
of the address range of the outputs / per DP slave	244 byte
service / as DP slave	
• DPV0	Yes
• DPV1	Yes
data volume	
 of the address range of the inputs / as DP slave / total 	240 byte
 of the address range of the outputs / as DP slave / total 	240 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
maximum	16; depending on the system upper limit
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	16
performance data / telecontrol	
protocol / is supported	
• TCP/IP	No
product functions / management, configuration, engineering	
configuration software	
• required	STEP 7 Professional V12 SP1 (TIA Portal) or higher
identification & maintenance function	C. E. T. T. C.
1&M0 - device-specific information	Yes
1&M1 – higher level designation/location designation	Yes
product functions / diagnostics	1.00
	Vec. via 97 1500 CDI I
product function / web-based diagnostics Yes; via S7-1500 CPU	
product functions / time	Vac
product function / pass on time synchronization	Yes
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
 to website: Industrial communication 	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
 to website: Image database 	http://automation.siemens.com/bilddb
to website: CAx-Download-Manager	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens

recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

1/24/2021