

3WA1106-2AF72-4EA4-Z C01+R10+T40



Withdrawable circuit breaker with guide frame, IEC 60947-2, frame size 1, 4-poles, N-pole left, In=630A up to 690V AC 50/60Hz, breaking capacity N Icu=55/42kA at 500/690V, Trip unit ETU600 LSIG upgrade ready , colordisplay, bluetooth and USB interface, Protection LT, ST, INST, GFx, include N-protection, (internal N-sensor available), incl. trip alarm switch (1xCO), rear connection horizontal, guide frame with shutter and position signall. switch (3xW), without Com & metering function with manual and motorized operating mechanism (M) 208-240 V AC / 220-250 V DC, Storage status and ready-to- dose signaling switches, Auxiliary switches 2NO+2NC, Closing coil (CC) 100% OP 208-240 V AC / 220-250 V DC, applicable for continuous duty, without Remote trip alarm reset coil (RR), without 2nd shunt trip, Shunt trip (ST) 100% OP 208-240 V AC / 220-250 V DC, suitable for continuous duty, Option C01 = Operations counter for circuit breaker Option R10 = Arc chute cover; for withdrawable breakers Not possible with breaking capacity C, E and D and frame size 2 4000A AC, Option T40 = Door sealing frame IP41

List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	3WA1106-2AF72-4EA4-Z C01+R10+T40
Product Description	Withdrawable circuit breaker with guide frame, IEC 60947-2, frame size 1, 4-poles, N-pole left, In=630A up to 690V AC 50/60Hz, breaking capacity N Icu=55/42kA at 500/690V, Trip unit ETU600 LSIG upgrade ready , colordisplay, bluetooth and USB interface, Protection LT, ST, INST, GFx, include N-protection, (internal N-sensor available), incl. trip alarm switch (1xCO), rear connection horizontal, guide frame with shutter and position signall. switch (3xW), without Com & metering function with manual and motorized operating mechanism (M) 208-240 V AC / 220-250 V DC, Storage status and ready-to-dose signaling switches, Auxiliary switches 2NO+2NC, Closing coil (CC) 100% OP 208-240 V AC / 220-250 V DC, applicable for continuous duty, without Remote trip alarm reset coil (RR), without 2nd shunt trip, Shunt trip (ST) 100% OP 208-240 V AC / 220-250 V DC, suitable for continuous duty, Option C01 = Operations counter for circuit breaker Option R10 = Arc chute cover; for withdrawable breakers Not possible with breaking capacity C, E and D and frame size 2 4000A AC, Option T40 = Door sealing frame IP41
Product family	3WA1 Air Circuit Breakers/Non-Aut. Air Circ. Br. up to 6300 A (AC), IEC
Product Lifecycle (PLM)	PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group	120 / 1CE
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	LAO-----

Delivery information

Export Control Regulations	ECCN : EAR99 / AL : N
Estimated dispatch time (Working Days)	5 Day/Days
Net Weight (kg)	72,273 Kg
Package size unit of measure	Not available
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	Not available
UPC	Not available
Commodity Code	85362090
LKZ_FDB/ CatalogID	LV10
Product Group	X01C
Group Code	P360
Country of origin	Czech Republic
Compliance with the substance restrictions according to RoHS directive	Since: 22.08.2019
Product class	B: return restricted, please contact your Siemens partner/contact
WEEE (2012/19/EU) Take-Back Obligation	No
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

Classifications

	Version	Classification
eClass	12	27-37-04-09
eClass	14	27-37-04-09
eClass	6	27-37-04-09
eClass	7.1	27-37-04-09
eClass	8	27-37-04-09
eClass	9	27-37-04-09
eClass	9.1	27-37-04-09
ETIM	7	EC000228
ETIM	8	EC000228
ETIM	9	EC000228

IDEA	4	4850
UNSPSC	15	39-12-16-01

;