

MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC  
3,5A FOOTPRINT FSA - 3X3.9MH NOT FOOTPRINT FOR V20



Figure similar

Order number	6SE6400-3CC00-4AD3
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	380 ... 480
Output current / Rated value	3.5 A
Active power loss	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	screw-type terminal
• for load-side outgoing feeder	Cable
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	6 mm <sup>2</sup>
• for load-side outgoing feeder	1.5 mm <sup>2</sup>
Cable length / of connecting cable / for load-side outgoing feeder	0.38 m
Type of electrical connection / for PE conductor	M5 screw studs
Protection class IP	IP20
Width	75.5 mm
Height	201 mm
Depth	50 mm
Net weight	1.3 kg
Certificate of suitability	cURus

### Further information

**Information und Download Center**

[https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order\\_form.aspx](https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx)

**Technical documentation**

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

**Industry Mall**

<https://eb.automation.siemens.com/mall/en/WW/Cataog/Product/6SE64003CC004AD3/all>

**Industry Online Support**

<http://support.automation.siemens.com/WW/view/en/6SE64003CC004AD3/all>