


SCALANCE XR324-4M PoE; Managed IE switch, 19" rack; 8x 10/100/1000 Mbit/s for RJ45 ports electrical with PoE, 8x 10/100/1000 Mbit/s for RJ45 ports electrical without PoE 4x 10/100/1000 Mbit/s 2-port media modules, electrical or optical; LED diagnostics; error signaling Contact; Select/set pushbutton, PROFINET IO device; C-plug in scope of delivery; Power supply 230 V AC; Ports at the back



product type designation	SCALANCE XR324-4M PoE
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
<ul style="list-style-type: none"> for network components or terminal equipment for Power-over-Ethernet / for network components or terminal equipment 	16; RJ45 8
number of 100 Mbit/s ST(BFOC) ports	
<ul style="list-style-type: none"> for multimode 	8
number of 100 Mbit/s SC ports	
<ul style="list-style-type: none"> for multimode 	8
number of 1000 Mbit/s LC ports	
<ul style="list-style-type: none"> for multimode for single mode (LD) 	8 8
interfaces / other	
number of electrical connections	
<ul style="list-style-type: none"> for operator console for signaling contact for media module for power supply 	1 1 4 1
type of electrical connection	
<ul style="list-style-type: none"> for operator console for signaling contact for power supply 	RJ11 2-pole terminal block 2-pole terminal block
design of the removable storage	
<ul style="list-style-type: none"> C-PLUG 	Yes
signal inputs/outputs	
operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> at DC / rated value 	24 V
operational current / of the signaling contacts	
<ul style="list-style-type: none"> at DC / maximum 	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage supply / redundant power supply unit	No
type of voltage / 1 / of the supply voltage	
<ul style="list-style-type: none"> supply voltage / 1 / rated value 	230 V

<ul style="list-style-type: none"> • power loss [W] / 1 / rated value • supply voltage / 1 / rated value • consumed current / 1 / maximum • type of electrical connection / 1 / for power supply • product component / 1 / fusing at power supply input 	<p>46 W</p> <p>85 ... 264 V</p> <p>1 A</p> <p>2-pole terminal block</p> <p>Yes</p>
ambient conditions	
<p>ambient temperature</p> <ul style="list-style-type: none"> • during operation • during storage • during transport • note 	<p>-40 ... +70 °C</p> <p>-40 ... +85 °C</p> <p>-40 ... +85 °C</p> <p>With vertical installation, the maximum operating temperature is reduced to 60 °C.</p>
<p>relative humidity</p> <ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum 	<p>95 %</p>
<p>protection class IP</p>	<p>IP20</p>
design, dimensions and weights	
<p>design</p>	<p>19" rack</p>
<p>number of modular height units / relating to 19-inch cabinet</p>	<p>1</p>
<p>width</p>	<p>449 mm</p>
<p>height</p>	<p>43.6 mm</p>
<p>depth</p>	<p>305 mm</p>
<p>net weight</p>	<p>6.8 kg</p>
<p>fastening method</p> <ul style="list-style-type: none"> • 19-inch installation • 35 mm top hat DIN rail mounting • wall mounting • S7-300 rail mounting • S7-1500 rail mounting 	<p>When used in shipbuilding, the device must be secured in the 19" rack at four points</p> <p>Yes</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
product features, product functions, product components / general	
<p>cascading in the case of a redundant ring / at reconfiguration time of <math>\sim 0.3\text{ s}</math></p>	<p>100</p>
<p>cascading in cases of star topology</p>	<p>any (depending only on signal propagation time)</p>
product functions / management, configuration, engineering	
<p>product function</p> <ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email • configuration with STEP 7 • RMON • port mirroring • multiport mirroring • CoS • PROFINET IO diagnosis 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
<p>PROFINET conformity class</p>	<p>B</p>
<p>product function / switch-managed</p>	<p>Yes</p>
<p>protocol / is supported</p> <ul style="list-style-type: none"> • Telnet • HTTP • HTTPS • TFTP • FTP • BOOTP • GMRP • DCP • LLDP 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>

<ul style="list-style-type: none"> • SNMP v1 	Yes
<ul style="list-style-type: none"> • SNMP v2 	Yes
<ul style="list-style-type: none"> • SNMP v3 	Yes
<ul style="list-style-type: none"> • IGMP (snooping/querier) 	Yes
identification & maintenance function	
<ul style="list-style-type: none"> • I&M0 - device-specific information 	Yes
<ul style="list-style-type: none"> • I&M1 – higher level designation/location designation 	Yes
product functions / diagnostics	
product function	
<ul style="list-style-type: none"> • port diagnostics 	Yes
<ul style="list-style-type: none"> • statistics Packet Size 	Yes
<ul style="list-style-type: none"> • statistics packet type 	Yes
<ul style="list-style-type: none"> • error statistics 	Yes
<ul style="list-style-type: none"> • SysLog 	Yes
product functions / VLAN	
product function	
<ul style="list-style-type: none"> • VLAN - port based 	Yes
<ul style="list-style-type: none"> • VLAN - protocol-based 	No
<ul style="list-style-type: none"> • VLAN - IP-based 	No
<ul style="list-style-type: none"> • VLAN dynamic 	Yes
number of VLANs / maximum	255
number of VLANs - dynamic / maximum	255
protocol / is supported / GVRP	Yes
product functions / DHCP	
product function	
<ul style="list-style-type: none"> • DHCP client 	Yes
<ul style="list-style-type: none"> • DHCP Option 82 	Yes
<ul style="list-style-type: none"> • DHCP Option 66 	Yes
<ul style="list-style-type: none"> • DHCP Option 67 	Yes
product functions / redundancy	
product function	
<ul style="list-style-type: none"> • ring redundancy 	Yes
<ul style="list-style-type: none"> • High Speed Redundancy Protocol (HRP) 	Yes
<ul style="list-style-type: none"> • high speed redundancy protocol (HRP) with redundancy manager 	Yes
<ul style="list-style-type: none"> • high speed redundancy protocol (HRP) with standby redundancy 	Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
<ul style="list-style-type: none"> • media redundancy protocol (MRP) with redundancy manager 	Yes
<ul style="list-style-type: none"> • redundancy procedure STP 	Yes
<ul style="list-style-type: none"> • redundancy procedure RSTP 	Yes
<ul style="list-style-type: none"> • redundancy procedure MSTP 	Yes
<ul style="list-style-type: none"> • passive listening 	Yes
protocol / is supported	
<ul style="list-style-type: none"> • STP/RSTP 	Yes
<ul style="list-style-type: none"> • STP 	Yes
<ul style="list-style-type: none"> • RSTP 	Yes
<ul style="list-style-type: none"> • MSTP 	Yes
<ul style="list-style-type: none"> • RSTP big network support 	Yes
<ul style="list-style-type: none"> • LACP 	Yes
product functions / security	
product function	
<ul style="list-style-type: none"> • ACL - MAC-based 	Yes
<ul style="list-style-type: none"> • ACL - port/MAC-based 	Yes
<ul style="list-style-type: none"> • IEEE 802.1x (radius) 	Yes
<ul style="list-style-type: none"> • broadcast/multicast/unicast limiter 	Yes

<ul style="list-style-type: none"> • broadcast blocking 	Yes
protocol / is supported	
<ul style="list-style-type: none"> • SSH 	Yes
product functions / time	
product function	
<ul style="list-style-type: none"> • SICLOCK support 	Yes
protocol / is supported	
<ul style="list-style-type: none"> • NTP • SNTP • IEEE 1588 profile default 	Yes Yes Yes
standards, specifications, approvals	
standard	
<ul style="list-style-type: none"> • for safety / from CSA and UL • for emitted interference • for interference immunity 	UL 508, CSA C22.2 No. 142-M1987 EN 61000-6-4:2007 (Class A) EN 61000-6-2:2006
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	-
<ul style="list-style-type: none"> • from CSA and UL 	No
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-2:2006, EN 61000-6-4:2007
<ul style="list-style-type: none"> • C-Tick • KC approval 	Yes Yes
standards, specifications, approvals / marine classification	
Marine classification association	
<ul style="list-style-type: none"> • French marine classification society (BV) • Korean Register of Shipping (KRS) 	Yes Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com . (V3.4)

last modified:

7/1/2021 